QUICK REFERENCE DATA

*SH1BE4M SERIES SPLIT SYSTEM HEAT PUMP WITH MICROCHANNEL COILS FOR MANUFACTURED HOUSING

14 SEER

| MODEL NUMBER: *SH1BE4M | | 1SP24K | 1SP30K | 1SP36K | 1SP42K | 1SP48K |
|---|-----------|--------|--------|--------|--------|--------|
| Recommended Refrigerant suction line O.D* NOTE: Liquid line is 3/8" O.D. for entire length. | 0-24 ft. | 3/4" | 3/4" | 7/8" | 7/8" | 7/8" |
| | 25-39 ft. | 3/4" | 3/4" | 7/8" | 7/8" | 7/8" |
| | 40-75 ft. | 3/4" | 3/4" | 7/8" | 7/8" | 7/8" |
| Refrigerant charge: (R-410A) in ounces for outdoor unit, indoor unit and 20' line set. (1) | | 97 | 104 | 111 | 124 | 122 |

(1) Additional charge for line sets above 20 feet. Values based on suction line as follows with 3/8" liquid line.

(a) 3/4" = 0.6 oz. per additional foot.

(b) 7/8" = 0.7 oz. per additional foot.

(c) 1 1/8" = 0.8 oz. per additional foot.

Table 1. Physical Data

| MODEL NUMBER: *SH1BE4M | | 1SP24K | 1SP30K | 1SP36K | 1SP42K | 1SP48K | |
|------------------------|---------------------|--|---------------------|----------------------|----------------------|----------------------|--|
| OD RESTRICTOR INSTALL | 0.042 | 0.051 | 0.055 | 0.057 | 0.060 | | |
| OUTDOOR UNIT BOM C | HARGE (OZ.) | 97 | 104 | 111 | 124 | 122 | |
| MODELS | SUPPLIED WITH ID | REQUIRED RESTRICTOR OR TXV (CHARGE ADDITION (OZ) / RATED AIRFLOW (SCFM)) | | | | | |
| C7-X | | | | | | | |
| C7B(A,H)MX24(C,U)-B | 669681 | 669681 (4 / 810) | | | | | |
| C7B(A,H)MX30(C,U)-B | 669682 | | 669682 (3 / 980) | | | | |
| C7B(A,H)MX30(C,U)-C | 669682 | 669682 (4 / 810) | 669682 (2 / 980) | | | | |
| C7B(A,H)MX36(C,U)-B | 669683 | | | 669683 (6 / 1140) | | | |
| C7B(A,H)MX36(C,U)-C | 669683 | | | 669683 (6 / 1140) | | | |
| C7B(A,H)MX42(C,U)-C | 669684 | | | | 669684 (0 / 1205) | | |
| C7B(A,H)MX48(C,U)-C | 669852 | | | | | 669852 (0 / 1510) | |

NOTES:

- Gray cells require the outdoor restrictor to be changed as well.
- The charges listed are only valid for the standard 20' lineset.
- Part numbers beginning with 669***are TXV part numbers and numbers listed as 0.*** are restrictor diameters.

THE CHARGE ADDITIONS PROVIDED IN THIS DOCUMENT ARE ESTIMATES BASED ON TEST DATA AND SHOULD ONLY BE A STARTING POINT. AFTER FOLLOWING THESE DIRECTIONS PLEASE ADJUST THE REFRIGERANT AMOUNT BASED ON THE APPROPRIATE CHARGING TABLES OR CHARTS IN THE INSTALLATION INSTRUCTIONS OR CHARGING LABEL.

Table 2. Restrictor or TXV / Charge Addition (Oz)

For other line set dimensions, refer to the Application Guidelines for Refrigerant Lines Addendum.

Instructions:

- 1. Find the column for the model of outdoor unit that is being installed.
- 2. Find the row for the model of the indoor unit that is being installed.
- 3. Find the cell in the table in which this row and column meet. In this cell the appropriate orifice / TXV and charge addition for this match are listed. If the text in this cell is BOLD, then a change of orifice is necessary.
- If a change in restrictor is necessary, then the appropriate restrictor will already be supplied with the outdoor unit.

Examples:

- For the *SH1BE4M1SP30K / C8(B,D)AMO1830U-B + TXV match, the appropriate TXV is the 920669A and no additional charge is necessary (NO CHANGES REQUIRED).
- For the *SH1BE4M1SP48K / C8(B,D)AMX49U-B match, the appropriate TXV is 669568 and no additional charge is neccessary. (NO CHANGES REQUIRED).

| MODEL NUMBER: *SH1BE4M | | 1SP24K | 1SP30K | 1SP36K | 1SP42K | 1SP48K | | |
|-------------------------------------|---------------------|--|----------------------|-----------------------|----------------------|----------------------|--|--|
| OD RESTRICTOR INSTALLED IN OD UNIT: | | 0.042 | 0.051 | 0.055 | 0.057 | 0.060 | | |
| OUTDOOR UNIT BOM CH | 97 | 104 | 111 | 124 | 122 | | | |
| MODELS | SUPPLIED WITH ID | REQUIRED RESTRICTOR OR TXV (CHARGE ADDITION (OZ) / RATED AIRFLOW (SCFM)) | | | | | | |
| C8+TXV | | | | | | | | |
| C8(B,D)AM01830U-B+TXV | 0.061 | 920668A (0 / 820) | 920669A (0 / 980) | | | | | |
| C8(B,D)AM036U-B+TXV | 0.067 | | | 920670A (0 / 1195) | | | | |
| C8-X | | | | | | | | |
| C8(B,D)AMX24U-B | 669564 | 669564 (0 / 810) | | | | | | |
| C8(B,D)AMX30U-B | 669565 | | 669565 (0 / 980) | | | | | |
| C8(B,D)AMX36U-B | 669566 | | | 669566 (0 / 1200) | | | | |
| C8(B,D)AMX42U-B | 669567 | | | | 669567 (0 / 1355) | | | |
| C8(B,D)AMX49U-B | 669568 | | | | | 669568 (0 / 1500) | | |

NOTES:

- · Gray cells require the outdoor restrictor to be changed as well
- The charges listed are only valid for the standard 20' lineset.
- Part numbers beginning with 669***are TXV part numbers and numbers listed as 0.*** are restrictor diameters.

THE CHARGE ADDITIONS PROVIDED IN THIS DOCUMENT ARE ESTIMATES BASED ON TEST DATA AND SHOULD ONLY BE A STARTING POINT. AFTER FOLLOWING THESE DIRECTIONS PLEASE ADJUST THE REFRIGERANT AMOUNT BASED ON THE APPROPRIATE CHARGING TABLES OR CHARTS IN THE INSTALLATION INSTRUCTIONS OR CHARGING LABEL.

Table 2. Restrictor or TXV / Charge Addition (Oz) - Continued