# GSH2BE4M SERIES SPLIT SYSTEM HEAT PUMP WITH MICROCHANNEL COILS FOR MANUFCTURED HOUSING

## 14 SEER

| MODEL NUMBER: GSH2BE4M   |           | 1RP24K | 1RP30K | 1SP36K | 1SP42K | 1SP48K |
|--|-----------|--------|--------|--------|--------|--------|
| <b>Refrigerant suction line O.D.*</b><br>NOTE: Liquid line is 3/8" O.D. for entire length.           | 0-24 ft.  | 3/4"   | 3/4"   | 7/8"   | 7/8"   | 7/8"   |
|  | 25-39 ft. | 3/4"   | 3/4"   | 7/8"   | 7/8"   | 7/8"   |
|  | 40-75 ft. | 3/4"   | 3/4"   | 7/8"   | 7/8"   | 7/8"   |
| <b>Refrigerant Charge:</b><br>(R-410A) in ounces for outdoor unit, indoor unit, and 20' line set (1) |           | 104    | 112    | 110    | 123    | 121    |

(1) Additional charge for line sets above 20 feet. Values based on suction line as follows with 3/8" liquid line.

(a) 3/4" = 0.6 oz. per additional foot.

(b) 7/8" = 0.7 oz. per additional foot.

(c) 1 1/8" = 0.8 oz. per additional foot.

\*For other line set dimensions, refer to the Application Guidelines for Refrigerant Lines Addendum.

| MODEL NUMBER: GSH2BE4M<br>OD RESTRICTOR INSTALLED IN OD UNIT:<br>OUTDOOR UNIT BOM CHARGE (OZ.) |                     | 1RP24K  | 1RP30K                | 1SP36K                | 1SP42K               | 1SP48K               |  |  |  |  |
|--|---------------------|---|-----------------------|-----------------------|----------------------|----------------------|--|--|--|--|
|  |                     | 0.043   | 0.049                 | 0.055                 | 0.057<br>123         | 0.060<br>121         |  |  |  |  |
|  |                     | 104   | 112                   | 110                   |                      |                      |  |  |  |  |
| MODELS   | SUPPLIED<br>WITH ID | REQUIRED RESTRICTOR OR TXV<br>(CHARGE ADDITION (OZ) / RATED AIRFLOW (SCFM)) |                       |                       |                      |                      |  |  |  |  |
| C8-X   |                     |   |                       |                       |                      |                      |  |  |  |  |
| C8(B,D)AMX24U-B  | 669564              | 669564<br>(0 / 850)   |                       |                       |                      |                      |  |  |  |  |
| C8(B,D)AMX30U-B  | 669565              |   | 669565<br>(0 / 1010)  |                       |                      |                      |  |  |  |  |
| C8(B,D)AMX36U-B  | 669566              |   |                       | 669566<br>(0 / 1200)  |                      |                      |  |  |  |  |
| C8(B,D)AMX42U-B  | 669567              |   |                       |                       | 669567<br>(0 / 1355) |                      |  |  |  |  |
| C8(B,D)AMX49U-B  | 669568              |   |                       |                       |                      | 669568<br>(0 / 1460) |  |  |  |  |
| C8+TXV   |                     |   |                       |                       |                      |                      |  |  |  |  |
| C8(B,D)AM01830U-B+TXV  | 0.061               | 920668A<br>(0 / 850)  | 920669A<br>(0 / 1010) |                       |                      |                      |  |  |  |  |
| C8(B,D)AM036U-B+TXV  | 0.067               |   |                       | 920670A<br>(0 / 1195) |                      |                      |  |  |  |  |

#### NOTES:

‡ Requires **REMOVAL** of refrigerant from unit.

• The charges listed are only valid for the standard 20' lineset.

• Part numbers beginning with 669\*\*\*are TXV part numbers and numbers listed as 0.\*\*\* are restrictor diameters.

THE CHARGE ADDITIONS PROVIDED IN THIS DOCUMENT ARE ESTIMATES BASED ON TEST DATA AND SHOULD ONLY BE A STARTING POINT. AFTER FOLLOWING THESE DIRECTIONS PLEASE ADJUST THE REFRIGERANT AMOUNT BASED ON THE APPROPRIATE CHARGING TABLES OR CHARTS IN THE INSTALLATION INSTRUCTIONS OR CHARGING LABEL.

# Table 2. Restrictor or TXV / Charge Addition (Oz)

## Instructions:

- 1. Find the column for the model of outdoor unit that is being installed.
- 2. Find the row for the model of the indoor unit that is being installed.
- 3. Find the cell in the table in which this row and column meet. In this cell the appropriate orifice / TXV and charge addition for this match are listed. If the text in this cell is BOLD, then a change of orifice is necessary.
- 4. If a change in restrictor is necessary, then the appropriate restrictor will already be supplied with the outdoor unit.

#### Examples:

- For the GSH2BE4M1RP30K / C(B,D)AMX30U-B the correct TXV is 669565 and no additional charge needs to be added (NO CHANGES NECESSARY).
- For the GSH2BE4M1SP36K / C8(B,D)AM036U-B+TXV the 920670A TXV is necessary and no additional charge needs to be added (TXV KIT).



Specifications & illustrations subject to change without notice or incurring obligations (08/20). O'Fallon, MO, © Nortek Global HVAC LLC 2020. All Rights Reserved. **1025274B** (Replaces 1025274A)

### **Table 1. Physical Data**