# **QUICK REFERENCE DATA**

## WSA2BD4M Series Residential Split System Air Conditioner

**13 SEER** 

MODEL NUMBER: WSA2BD4M		1SN36(C,D)	1SN48(C,D)	1SN60(C,D)
REFRIGERANT SUCTION LINE O.D* NOTE: Liquid line is 3/8" O.D. for entire length.	0-24 ft.	3/4"	7/8"	7/8"
	25-39 ft.	7/8" (1)	7/8"	1-1/8" (2)
	40-75 ft.	7/8" (1)	7/8"	1-1/8" (2)
REFRIGERANT CHARGE: (R-410A) in ounces for outdoor unit, indoor unit, and 15' line set (3)		66	84	78

- (1) Requires 7/8" to 3/4" reducer from line to unit.
- (2) Requires 1-1/8" to 7/8" reducer from line to unit.
- (3) Additional charge for line sets above 15 feet. Values based on suction line as follows with 3/8" liquid line.
  - (a) 3/4" = 0.6 oz. per additional foot.
  - (b) 7/8" = 0.7 oz. per additional foot.
  - (c)  $1 \frac{1}{8}$ " = 0.8 oz. per additional foot.

### **Table 1. Physical Data**

#### **Instructions:**

- 1. Find the column for the model of outdoor unit that is being installed.
- 2. Find the row for the model of the indoor unit that is being installed.
- 3. Find the cell in the table in which this row and column meet. In this cell the appropriate orifice / TXV and charge addition for this match are listed. If the text in this cell is BOLD, then a change of orifice is necessary.
- 4. If a change in restrictor is necessary, then the appropriate restrictor will already be supplied with the outdoor unit.

#### **Examples:**

- For the WSA2BD4M1SN36(C,D) / C7B(A,H)M03642(C,U)-B match the restrictor needs to be changed to a 0.067" and no additional charge needs to be added (CHANGE IN RESTRICTOR).
- For the WSA2BD4M1SN60(C,D) / B6BMM060K-C match the correct restrictor is the 0.087" and no additional charge needs to be added (NO CHANGES REQUIRED).

MODEL NUMBER: WSA2BD4M		1SN36(C,D)	1SN48(C,D)	1SN60(C,D)			
ID RESTRICTOR SUPPLIED WITH OD UNIT:		0.067	0.080	0.085			
OUTDOOR UNIT BOM CHARGE (OZ.):		66	84	78			
MODELS	SUPPLIED WITH ID	REQUIRED RESTRICTOR OR TXV (CHARGE ADDITION (OZ) / RATED AIRFLOW (SCFM))					
В6ВММО							
B6BMM036K-B	0.067	0.067 (0 / 1210)					
B6BMM048K-C	0.079		0.079 (-5 / 1625) ‡				
B6BMM060K-C	0.087			0.087 (0 / 1595)			
C6							
C6B(A,H)-X60(C,U)-C	669686			669686 (22 / 1420)			
C7-0							
C7B(A,H)M03642(C,U)-B	0.071	0.067 (0 / 1150)					
C7B(A,H)M03648(C,U)-C	0.067	0.067 (0 / 1150)	0.080 (0 / 1360)				
C7B(A,H)M060(C,U)-C	0.083			0.085 (0 / 1500)			
C7B(A,H)M060(C,U)-D	0.083			0.085 (0 / 1500)			

#### NOTES

THE CHARGE ADDITIONS PROVIDED IN THIS DOCUMENT ARE ESTIMATES BASED ON TEST DATA AND SHOULD ONLY BE A STARTING POINT. AFTER FOLLOWING THESE DIRECTIONS PLEASE ADJUST THE REFRIGERANT AMOUNT BASED ON THE APPROPRIATE CHARGING TABLES OR CHARTS IN THE INSTALLATION INSTRUCTIONS OR CHARGING LABEL.

<sup>\*</sup>For other line set dimensions, refer to the Application Guidelines for Refrigerant Lines Addendum.

<sup>‡</sup> Requires **REMOVAL** of refrigerant from unit.

#### **Instructions:**

- 1. Find the column for the model of outdoor unit that is being installed.
- 2. Find the row for the model of the indoor unit that is being installed.
- Find the cell in the table in which this row and column meet. In this cell
  the appropriate orifice / TXV and charge addition for this match are listed.
  If the text in this cell is BOLD, then a change of orifice is necessary.
- 4. If a change in restrictor is necessary, then the appropriate restrictor will already be supplied with the outdoor unit.

#### **Examples:**

- For the WSA2BD4M1SN36(C,D) / C7B(A,H)M03642(C,U)-B match the restrictor needs to be changed to a 0.067" and no additional charge needs to be added (CHANGE IN RESTRICTOR).
- For the WSA2BD4M1SN60(C,D) / B6BMM060K-C match the correct restrictor is the 0.087" and no additional charge needs to be added (NO CHANGES REQUIRED).

MODEL NUMBER WOARD	484	40N00(0 D)	40N40(0 D)	40N00(0 D)		
MODEL NUMBER: WSA2BD4M		1SN36(C,D)	1SN48(C,D)	1SN60(C,D)		
ID RESTRICTOR SUPPLIED WITH OD UNIT:		0.067	0.080	0.085		
OUTDOOR UNIT BOM CHARGE (OZ.):		66	84	78		
MODELS	SUPPLIED WITH ID	REQUIRED RESTRICTOR OR TXV (CHARGE ADDITION (OZ) / RATED AIRFLOW (SCFM))				
C7-X						
C7B(A,H)MX36(C,U)-C	669683	669683 (-11 / 1100) ‡				
C7B(A,H)MX48(C,U)-C	669852		669852 (-16 / 1400) ‡			
C7B(A,H)MX48(C,U)-D	669852		669852 (-16 / 1400) ‡			
C7B(A,H)MX60(C,U)-C	669686			669686 (0 / 1695)		
C7B(A,H)MX60(C,U)-D	669686			669686 (0 / 1695)		

#### NOTES:

THE CHARGE ADDITIONS PROVIDED IN THIS DOCUMENT ARE ESTIMATES BASED ON TEST DATA AND SHOULD ONLY BE A STARTING POINT. AFTER FOLLOWING THESE DIRECTIONS PLEASE ADJUST THE REFRIGERANT AMOUNT BASED ON THE APPROPRIATE CHARGING TABLES OR CHARTS IN THE INSTALLATION INSTRUCTIONS OR CHARGING LABEL.

**Table 2. Continued** 

<sup>‡</sup> Requires REMOVAL of refrigerant from unit.