BROAN® HEATING AND COOLING SYSTEMS Product Line



All packaged systems feature Anteater® or Anteater MC® Micro-Channel evaporator coils

97+% GAS FURNACES

All gas furnaces feature SmartLite® Control Boards

FG7MQ
97+ AFUE Ultra High Efficiency, Fully Modulating, Condensing, Upflow/Horizontal Gas Furnace, iSEER® technology, iQ Drive® Ready, 60,000 - 120,000 BTUH Input, Variable-Speed Blower



95.1% GAS FURNACES

FG7T(C, L)-VS
95.1 AFUE Extra High Efficiency, Direct Vent or Non-Direct Vent, Condensing, 2-Stage (Upflow/Horizontal, Downflow) Gas Furnace, iSEER technology, iQ Drive Ready, 60,000 - 120,000 BTUH Input, Variable-Speed Blower



FG7T(C, L)-FS
95.1 AFUE Extra High Efficiency, Direct Vent or Non-Direct Vent, Condensing, 2-Stage (Upflow/Horizontal, Downflow) Gas Furnace, iSEER ECM Blower technology, 60,000 - 120,000 BTUH Input



95% GAS FURNACES

FG7S(D, M)
95 AFUE Extra High Efficiency, Direct Vent or Non-Direct Vent, Condensing, 1-Stage (Upflow/Horizontal, Downflow) Gas Furnace, Multi-Speed PSC Blower Motor, (38,000 - 120,000, 54,000 - 118,000) BTUH Input



92.1% GAS FURNACES

FG7S(C, L)
92.1 AFUE Extra High Efficiency, Direct Vent or Non-Direct Vent, Condensing, 1-Stage (Upflow/Horizontal, Downflow) Gas Furnace, Multi-Speed PSC Blower Motor, (38,000 - 120,000, 54,000 - 120,000) BTUH Input



80% GAS FURNACES

FG7T(A, K)-VS
80 AFUE High Efficiency, 2-Stage (Upflow/Horizontal, Downflow) Gas Furnace, iSEER technology, iQ Drive Ready, 60,000 - 140,000 BTUH Input, Variable-Speed Blower



FG7T(A, K)-FS
80 AFUE High Efficiency, 2-Stage (Upflow/Horizontal, Downflow) Gas Furnace, iSEER ECM Blower technology, 60,000 - 140,000 BTUH Input

FG7S(A, K)
80 AFUE High Efficiency, 1-Stage (Upflow/Horizontal, Downflow) Gas Furnace, Multi-Speed PSC Blower Motor, (45,000 - 126,000, 54,000 - 126,000) BTUH Input



95.1% GAS FURNACES

KG7T(C, L)-FS
95.1 AFUE Extra High Efficiency, Direct Vent or Non-Direct Vent, Condensing, 2-Stage (Upflow/Horizontal, Downflow) Gas Furnace, iSEER ECM Blower technology, 60,000 - 120,000 BTUH Input



95% GAS FURNACES

KG7SD-E
Up to 95 AFUE Extra High Efficiency, Direct Vent or Non-Direct Vent, Condensing, 1-Stage Upflow/Horizontal, Gas Furnace, iSEER ECM Blower technology, 38,000 - 120,000 BTUH Input



95%/92.1% GAS FURNACES

KG7S(D,M)/KG7S(C, L)
95 AFUE/92.1 AFUE Extra High Efficiency, Direct Vent or Non-Direct Vent, Condensing, 1-Stage (Upflow/Horizontal, Downflow) Gas Furnace, Multi-Speed PSC Blower Motor, (38,000 - 120,000, 54,000 - 118,000)/ (38,000 - 120,000, 54,000 - 120,000) BTUH Input



80% GAS FURNACES

KG7T(A, K)-FS
80 AFUE High Efficiency, 2-Stage (Upflow/Horizontal, Downflow) Gas Furnace, iSEER ECM Blower technology, 60,000 - 140,000 BTUH Input

KG7S(A, K)
80 AFUE High Efficiency, 1-Stage (Upflow/Horizontal, Downflow) Gas Furnace, Multi-Speed PSC Blower Motor, (45,000 - 126,000, 54,000 - 126,000) BTUH Input



PACKAGED SYSTEMS

All gas/electric and iHybrid® packaged systems feature SmartLite Control Boards

R6GI
Ultra High Efficiency, Single Packaged Gas/Electric, iQ Drive® Technology, functions with 2-Stage Gas Heat/5-Stage Cooling output from 2-Stage thermostat, Variable-Speed ECM Blower, Square Duct Connections, Convertible Airflow, 20 SEER, 81% AFUE, Up to 13 EER, 2 - 5 Ton, 80,000 - 120,000 BTUH Input



R6GF-B
Single Packaged Gas/ Electric, 2-Stage Heat & Cool, Variable-Speed Blower, Square Duct Connections, Convertible Airflow, 15 SEER, 81% AFUE, 12 EER, 2 - 5 Ton, 80,000 - 120,000 BTUH Input



DF6SF-B
Single Packaged iHybrid Dual Fuel, 2-Stage Gas Heat/2-Stage Cooling, Variable-Speed Blower, Square Duct Connections, Convertible Airflow, 15 SEER, 81% AFUE, 8.0 HSPF, 12 EER, 2 - 5 Ton, 80,000 - 120,000 BTUH Input



R8HE-A
Single Packaged Gas/ Electric, 2-Stage Heat, Variable-Speed ECM Blower, Square Duct Connections, Convertible Airflow, 14 SEER, 95% AFUE, up to 12 EER, 2 - 5 Ton, 60,000 - 96,000 BTUH Input



PACKAGED SYSTEMS

R8GE
Single Packaged Gas/Electric, Square Duct Connections, Convertible Airflow, 14 SEER,81% AFUE, 11 EER, 2 - 5 Ton, 45,000 - 120,000 BTUH Input



P5RF-A/Q5RF-A
Single Packaged Air Conditioner/Heat Pump, 2-Stage, ECM Blower, Round Duct Connections, 15 SEER/8.0 HSPF, 12 EER, 2 - 5 Ton



P8SE/Q6SE
Single Packaged Air Conditioner/Heat Pump, Square Duct Connections, Convertible Airflow, 14 SEER/8.0 HSPF, up to 11.5 EER/11 EER, 3, 4 and 5 Ton



P7RE/Q7RE
Single Packaged Air Conditioner\Heat Pump, Round Duct Connections, 14 SEER/8.0 HSPF, 11 EER, 2 - 5 Ton



ENERGY STAR® certification is awarded to products designed to reduce energy consumption and utility costs.

To qualify, packaged systems must have a Seasonal Energy Efficiency Ratio (SEER) rating of 15.0 or higher and an Energy Efficiency Ratio (EER) of 12.0 or higher. Packaged heat pumps must also have a Heating Seasonal Performance Factor (HSPF) of 8.2 or higher.

Split system air conditioners and heat pumps must have a 15.0 SEER rating or higher and an EER of 12.5 or higher. Split system heat pumps must also have an HSPF of 8.5 or higher.



BROAN UNITS OFFER A 10-YEAR LIMITED WARRANTY ON ALL PARTS WHEN REGISTERED. PLUS THE BROAN QUALITY PLEDGE ON SELECT MODELS, WHICH STATES IF WITHIN THE FIRST 10 YEARS THE COMPRESSOR OR FURNACE HEAT EXCHANGER FAILS BROAN WILL REPLACE THE ENTIRE UNIT, REGISTRATION REQUIRED. AIR HANDLERS AND COILS CARRY A 5-YEAR ALL PARTS LIMITED WARRANTY AND WHEN INSTALLED WITH A MATCHED OUTDOOR UNIT, WILL CARRY THE OUTDOOR SYSTEM WARRANTY. SEE WARRANTY FOR DETAILS.

SPLIT SYSTEM AIR CONDITIONERS

FS4BG
Ultra High Efficiency, 20 SEER, Air Conditioner, iQ Drive® Technology, 2, 3, 4 and 5 Ton Capacity, Micro-Channel

FS4BF
Extra High Efficiency, Up to 16 SEER, 2-Stage, Air Conditioner, 2, 3, 4 and 5 Ton Capacity, Micro-Channel

FS4BE
Extra High Efficiency, Up to 15 SEER, Air Conditioner, 1-1/2 - 5 Ton Capacity, Micro-Channel

FS4BD
High Efficiency, Up to 14 SEER, Air Conditioner, 1-1/2 - 5 Ton Capacity, Micro-Channel



SPLIT SYSTEM HEAT PUMPS

FT4BG
Ultra High Efficiency, Up to 19 SEER, 10.0 HSPF, Heat Pump, iQ Drive Technology, 2, 3, 4 and 5 Ton Capacity

FT4BF
Extra High Efficiency, Up to 16 SEER, 9.0 HSPF, 2-Stage, Heat Pump, 2, 3, 4 and 5 Ton Capacity

FT4BE
High Efficiency, Up to 15 SEER, 8.5 HSPF, Heat Pump, 1-1/2 - 5 Ton Capacity, Micro-Channel



AIR HANDLERS

B6VMAX
Multi-Poised, Vertical/Horizontal, Variable-Speed, Air Handler, TXV, Anteater®

B6BMMX
Multi-Poised, Vertical/Horizontal, Multi-Speed, Air Handler, TXV, Anteater MC® Micro-Channel

B6BMM0
Multi-Poised, Multi-Speed, Air Handler, Anteater MC Micro-Channel

B6EMMX
ECM Fixed-Speed Motor, Multi-Poised, Air Handler, TXV, Anteater MC Micro-Channel



AIR HANDLERS

B6VMMX
ECM Variable-Speed Motor, Multi-Poised, Air Handler, TXV, Anteater MC Micro-Channel

B6BW
Vertical Wall Mount, Air Handler, Anteater MC Micro-Channel

B6EW
Vertical Wall Mount, Multi-Speed, ECM Motor, Air Handler, TXV, Anteater MC Micro-Channel

MB7BM
Multi-Poised, Multi-Speed Modular Blower (matched with a cased coil easily creates a 2 piece Air Handler)

MB7EM
Energy Efficient Model

MB7VM
Variable-Speed Model



INDOOR COILS

C7BAM0
Anteater MC Micro-Channel

A, B, C and D sizes available in various capacities

C7BHM0
Anteater MC Micro-Channel

A, B, C and D sizes available in various capacities

Cased & Vertical/ Horizontal, Multi-poised versions available

C7BAMX
Factory-installed TXV, Anteater MC Micro-Channel

A, B, C and D sizes available in various capacities

C7BHMX
Factory-installed TXV, Anteater MC Micro-Channel

A, B, C and D sizes available in various capacities

Cased & Vertical/ Horizontal, Multi-poised versions available

C6BH-X
A, B, C and D sizes available in various capacities, Anteater

Cased Horizontal



BROAN®
HEATING AND COOLING SYSTEMS

Specifications and illustrations subject to change without incurring obligation.

www.broanhvac.net

Broan® trademark used under license. iHybrid®, iSEER®, iQ Drive®, ecoLogic®, SmartLite®, Anteater® and Anteater MC® are registered trademarks of Nortek Global HVAC, LLC.
© Nortek Global HVAC, LLC 2016. All Rights Reserved. 164D-0416