

**MAYTAG**

## TECHNICAL SPECIFICATIONS

**iQ Drive<sup>®</sup>**

*Model PSH4BI Series*



M1200 Product Line

**R-410A Ultra High Efficiency Heat Pump  
22.0 SEER — 2-3-4 Ton Capacity**

- **M1200 – 12 YEAR ALL PARTS LIMITED WARRANTY**
- **M1200 WITH UPGRADED WARRANTY PACKAGE - 12 YEAR ALL PARTS & LABOR LIMITED WARRANTY**
- **Both the standard and upgraded limited warranty packages offer a 12 Year Dependability Promise to replace the entire unit, if the unit's major component (heat exchanger or compressor) fails within the first 12 years of operation, to the original owner. All split system products must be installed with a matched indoor air handler or indoor coil to qualify.**
- **Product registration (by consumer or dealer) required for 12-year Warranty and Dependability Promise within a limited period of time after the installation. See current warranty document for details. This can be viewed at [www.maytagvac.com](http://www.maytagvac.com) or ask your sales representative.**
- **Dealer is responsible for registration of labor portion of warranty.**



The iQ Drive® Heat Pump System features fully variable speed compressor technology and variable speed indoor and outdoor motors. The system provides variable cooling capacity as needed. It operates near the nominal rated capacity at the thermostat set point and modulates as temperature difference between set point and room temperature changes. The system may run at additional 18% capacity to provide rapid cooling or heating. The system has a built-in humidity control that will activate humidifier equipment (if supplied), and reduces blower speed if indoor relative humidity is greater than set point (default set at 60%).


### Features and Benefits

- **iQ Drive** – Inverter driven Panasonic rotary compressor which provides fully variable operation.
- **R-410A Refrigerant** – Environmentally friendly non-ozone depleting refrigerant.
- **Designed using galvanized steel** – with a polyester urethane coat finish. The 950 hour salt spray finish resists corrosion 50% better than comparable units.
- **Copper Tube / Aluminum Fin Coils** – Both indoor and outdoor coils are designed to optimize heat transfer, minimize size and cost, and increase durability and reliability.
- **Permanently Lubricated Motor** – A heavy duty brushless motor for long lasting reliability and quiet operation. Requires no maintenance and is completely protected from rain and snow.
- **Compressor Sound Blanket** – Engineered to significantly reduce unwanted compressor noise.
- **Swept-Wing Fan Blade** – Engineered to provide quiet operation. The specific energy absorbing hub is designed to reduce noise while operating through various frequencies.
- **Louvered Condenser Guard** – Durable metal guard protects the coil from yard hazards and extreme weather.
- **Removable Top Grille Assembly** – Allows ease of service from the top without disconnecting fan motor leads.
- **High Pressure Switch** – Protects against abnormally high system pressures. Auto-reset feature prevents nuisance service visits.
- **Low Pressure Switch** – Protects against loss of system refrigerant charge.
- **Liquid Line Filter Drier** – Included with unit, field installed.
- **One Piece Top/Orifice** – Designed for maximum airflow and quiet operation.
- **Easy Compressor and Control Access** – Designed to make servicing easier for the contractor, access panels are provided to all controls and the compressor from the side of the unit.
- **Highest Efficiency with the lowest Sound Levels** – Up to 22 SEER with sound ratings of 59-72dB depending upon operating conditions.


# DIMENSIONS/OUTDOOR SECTION

## 22 SEER — Ultra High Efficiency

PSH4BI	024K	036K	048K
H	37	41	45
W	31 1/4	31 1/4	31 1/4
D	31 1/4	31 1/4	31 1/4



# IDENTIFICATION CODE



# PHYSICAL AND ELECTRICAL SPECIFICATIONS/OUTDOOR UNITS

## 22 SEER — Ultra High Efficiency

Model Number PSH4BI-		024K	036K	048K		
Electrical Data	Volts-Cycles-Phase (1)	208/230-60-1	208/230-60-1	208/230-60-1		
	Total Amps	13.0	18.0	22.0		
	Delay Fuse Max. (2)	25	35	45		
	Min. Circuit Ampacity	16.6	22.9	27.1		
Condenser Data	Coil	Area(ft <sup>2</sup> )	20.3	22.8	25.4	
		Rows-FPI	1 - 20	1 - 20	1 - 20	
		Tube Dia	3/8" O.D.	3/8" O.D.	3/8" O.D.	
	Fan Motor	Type	Brushless DC	Brushless DC	Brushless DC	
		Amps	1.6	1.6	1.6	
		HP	0.5	0.5	0.5	
	Fan Blade	Dia-# Blades	24" - 2	24" - 2	24" - 2	
		SCFM	3200	3400	3600	
	Compressor Data		RLA	11.4	16.4	20.4
	Refrigerant suction line O.D. (all length of liquid line are 3/8" O.D.)		0-24 ft.	3/4"	7/8"	7/8"
25-39 ft.			3/4"	7/8"	1 1/8" (3)	
40-75 ft.			7/8"(3)	1 1/8" (3)	1 1/8" (3)	
Refrigerant charge (R-410A) in ounces for outdoor unit, indoor unit and 15' lineset.		171	203	203		
Weight	Net	190	220	225		
	Approximate (lbs.)	Ship	200	230	235	

- (1) Operating Voltage Range: 187v min. — 253v max.  
 (2) HACR Type Circuit Breakers may be used.  
 (3) Requires Reducer.

**Note:**

**Refrigerant Tubing Limitations-**The compressor manufacturer imposes a maximum equivalent line set length of 100ft. Furthermore, vertical elevation shall not exceed 50 ft.

COPPER WIRE SIZE — AWG (1% Voltage Drop)				
Supply Wire Length-Feet				Supply Circuit
200	150	100	50	Ampacity
6	8	10	14	15
4	6	8	12	20
4	6	8	10	25
4	4	6	10	30
3	4	6	8	35
3	4	6	8	40
2	3	4	6	45
2	3	4	6	50

Wire Size based on N.E.C. for 60° type copper conductors.

## SYSTEM COOLING CAPACITIES

### 22 SEER — Ultra High Efficiency — Single Phase

Outdoor Unit Model Number PSH4BI-	Indoor Unit	Range Cooling Capacity @95° OD BTUH	EER @ Nominal Capacity	SEER	Nominal Capacity	Range SCFM
024K	B6VMAI24KB	11,300-26,900	14.6	22	22,800	500-950
036K	B6VMAI36KB	14,200-40,700	13.0	21	35,000	680-1110
048K	B6VMAI48KC	14,300-48,000	12.5	21	44,500	725-1800

Minimum operating ambient temperature is 40°F

**NOTE:** Each system was operated at its nominal capacity.

Indoor conditions were 80F° dry-bulb temperature and 67F° wet-bulb temperature (approx. 51% relative humidity, 95° outdoor temperature.)

## SYSTEM HEATING CAPACITIES

### 22 SEER — Ultra High Efficiency — Single Phase

Outdoor Unit Model Number PSH4BI-	Indoor Unit	Range Heating Capacity @47° OD BTUH	Nominal Capacity	HSPF	COP @ Nominal Capacity	CFM
024K	B6VMAI24KB	6,500-24,100	22,400	10	3.9	500-950
036K	B6VMAI36KB	11,300-39,900	34,000	9.6	3.4	680-1110
048K	B6VMAI48KC	11,400-47,800	46,000	10	3.6	725-1800

Minimum operating ambient temperature is 12°F

**NOTE:** Each system was operated at its nominal capacity.

Indoor conditions were 70F° dry-bulb temperature and 47F° dry bulb temperature, 43F° wet bulb outdoor temperature

**See current AHRI Directory for certified combinations and ratings.**

www.ahridirectory.org

# EXPANDED RATINGS - 2 TON WITH G7 FURNACE B CABINET

## COOLING

Outdoor Temperature:		60°F			70°F			80°F			90°F			95°F			100°F			110°F			120°F		
		Total Capacity	Sensible Capacity	kW	Total Capacity	Sensible Capacity	kW	Total Capacity	Sensible Capacity	kW	Total Capacity	Sensible Capacity	kW	Total Capacity	Sensible Capacity	kW	Total Capacity	Sensible Capacity	kW	Total Capacity	Sensible Capacity	kW	Total Capacity	Sensible Capacity	kW
Speed	Indoor Tdb - in	13.5	13.5	0.36	12.9	0.43	12.2	12.2	0.52	11.5	11.5	0.64	11.1	11.1	0.71	10.7	10.7	0.77	9.8	9.8	0.92	8.8	8.8	1.08	
		14.2	11.4	0.34	13.4	0.43	12.6	10.5	0.53	11.8	10.1	0.64	11.4	9.9	0.70	10.9	9.7	0.76	10.1	9.3	0.89	9.1	8.9	1.03	
Minimum	80	15.2	9.0	0.30	14.8	0.38	13.8	8.4	0.49	12.8	8.0	0.61	12.2	7.8	0.68	11.7	7.5	0.74	10.5	7.0	0.90	9.3	6.4	1.06	
	75	12.7	11.5	0.36	12.0	0.43	11.3	10.7	0.53	10.5	10.3	0.65	10.1	10.0	0.71	9.7	9.7	0.78	8.8	8.8	0.93	7.9	7.9	1.09	
	80	17.3	17.3	0.56	16.6	0.66	15.8	15.8	0.77	15.0	15.0	0.91	14.5	14.5	1.00	14.1	14.1	1.07	13.1	13.1	1.27	12.0	12.0	1.48	
Intermediate	80	18.6	14.2	0.50	17.7	0.62	16.7	13.3	0.76	15.7	12.9	0.90	15.1	12.6	0.98	14.6	12.4	1.06	13.5	11.9	1.23	12.4	11.4	1.40	
	80	20.0	11.2	0.52	19.1	0.61	18.2	10.6	0.73	17.0	10.1	0.88	16.4	9.8	0.96	15.8	9.6	1.05	14.4	9.0	1.26	12.9	8.3	1.49	
	75	16.5	14.1	0.55	15.7	0.65	14.8	13.3	0.77	13.9	12.8	0.90	13.5	12.6	0.99	13.0	12.3	1.06	12.0	11.7	1.25	10.9	10.9	1.45	
	80	25.0	24.0	1.01	23.9	0.35	22.9	22.9	1.37	21.9	21.9	1.56	21.3	21.3	1.65	20.7	20.7	1.76	19.5	19.5	1.95	18.1	18.1	2.14	
	80	27.1	18.9	0.98	25.9	0.87	24.6	18.4	1.33	23.3	18.0	1.53	22.6	17.7	1.64	21.9	17.4	1.75	20.4	16.6	1.97	18.9	15.7	2.22	
Nominal	80	29.4	16.1	0.99	28.1	1.16	26.6	15.1	1.34	25.2	14.5	1.53	24.3	14.2	1.62	23.5	14.0	1.71	21.6	13.2	1.89	19.7	12.4	2.07	
	75	24.1	19.6	1.00	23.1	1.16	22.0	18.6	1.35	20.8	18.1	1.54	20.1	17.8	1.63	19.5	17.5	1.74	18.1	16.8	1.92	16.6	16.0	2.13	
	80	30.0	27.8	1.36	28.6	2.71	27.2	26.5	1.80	25.8	25.7	2.04	25.2	25.2	2.16	24.6	24.6	2.28	23.1	23.1	2.53	21.4	21.4	2.76	
Maximum	80	32.0	23.2	1.39	30.6	2.26	29.2	22.1	1.80	27.7	21.5	2.03	26.9	21.2	2.16	26.1	20.8	2.28	24.4	20.1	2.55	22.6	19.2	2.84	
	80	35.3	18.8	1.33	33.7	1.82	32.0	17.6	1.78	30.1	16.9	2.02	29.1	16.5	2.13	28.1	16.1	2.25	25.9	15.3	2.46	23.6	14.3	2.67	
	75	28.9	22.8	1.34	27.6	2.21	26.3	21.4	1.77	24.8	20.8	2.01	24.0	20.4	2.13	23.3	20.1	2.25	21.6	19.3	2.50	19.9	18.5	2.74	

Note: Capacity and Sensible Capacity are shown in units of thousands of Btu/h.

## HEATING

Outdoor Temperature:		12°F			17°			20°			30°			40°			47°			50°			60°		
		Total Capacity	COP	kW	Total Capacity	COP	kW	Total Capacity	COP	kW	Total Capacity	COP	kW	Total Capacity	COP	kW	Total Capacity	COP	kW	Total Capacity	COP	kW	Total Capacity	COP	kW
Speed	Indoor Tdb - °F	2.2	1.79	0.36	2.8	2.31	0.36	3.2	2.62	0.36	4.5	3.70	0.35	5.8	4.80	0.36	6.7	5.80	0.34	7.2	6.12	0.34	8.4	7.51	0.33
Minimum	70	2.0	1.40	0.42	2.7	1.84	0.42	3.0	2.10	0.42	4.3	3.01	0.42	5.5	3.97	0.41	6.4	4.69	0.40	6.8	5.01	0.40	8.0	6.16	0.38
	80	1.9	1.14	0.50	2.6	1.51	0.50	2.8	1.68	0.50	4.0	2.39	0.49	5.3	3.18	0.49	6.0	3.73	0.47	6.5	4.05	0.47	7.6	4.90	0.46
Intermediate	60	6.8	3.20	0.62	7.6	3.45	0.64	8.0	3.67	0.64	9.6	4.27	0.66	11.2	4.90	0.67	12.4	5.43	0.67	12.9	5.65	0.67	14.7	6.51	0.66
	70	6.5	2.63	0.73	7.3	2.86	0.74	7.7	3.01	0.75	9.2	3.51	0.77	10.8	4.05	0.78	11.9	4.46	0.78	12.4	4.65	0.78	14.1	5.34	0.77
	80	6.3	2.21	0.84	7.0	2.39	0.85	7.4	2.52	0.86	8.8	2.93	0.88	10.3	3.38	0.89	11.4	3.75	0.89	11.9	3.91	0.89	13.5	4.47	0.88
Nominal	60	11.2	2.48	1.32	13.2	2.87	1.35	13.8	2.96	1.37	17.2	3.56	1.42	20.6	4.03	1.50	22.9	4.40	1.53	24.0	4.57	1.54	27.4	5.00	1.60
	70	10.8	2.13	1.48	12.4	2.41	1.51	13.4	2.56	1.53	16.7	3.05	1.60	19.9	3.50	1.67	22.2	3.81	1.71	23.2	3.93	1.73	26.5	4.31	1.80
	80	10.4	1.84	1.66	12.4	2.14	1.70	12.9	2.20	1.72	16.1	2.63	1.79	19.3	3.03	1.87	21.4	3.26	1.92	22.5	3.41	1.93	25.7	3.73	2.02
Maximum	60	14.6	2.83	1.51	16.0	3.05	1.54	16.9	3.20	1.54	19.6	3.60	1.60	22.5	4.03	1.64	24.6	4.32	1.67	25.6	4.45	1.69	28.7	4.85	1.73
	70	14.1	2.47	1.67	15.4	2.65	1.70	16.2	2.76	1.72	18.9	3.13	1.77	21.7	3.50	1.82	23.7	3.75	1.86	24.6	3.86	1.87	27.6	4.22	1.92
	80	13.5	2.13	1.86	14.8	2.30	1.88	15.6	2.41	1.90	18.2	2.72	1.96	20.8	3.03	2.01	22.8	3.25	2.06	23.6	3.36	2.06	26.5	3.67	2.12

# EXPANDED RATINGS - 3 TON WITH G7 FURNACE B CABINET

## COOLING

Outdoor Temperature:		60°F			70°F			80°F			90°F			95°F			100°F			110°F			120°F				
		Total Capacity	Sensible Capacity	kW	Total Capacity	Sensible Capacity	kW	Total Capacity	Sensible Capacity	kW	Total Capacity	Sensible Capacity	kW	Total Capacity	Sensible Capacity	kW	Total Capacity	Sensible Capacity	kW	Total Capacity	Sensible Capacity	kW	Total Capacity	Sensible Capacity	kW		
Speed	Indoor Tdb - in Twb - in																										
	80	62	16.2	16.2	0.44	15.4	15.4	0.55	14.5	14.5	0.66	13.8	13.8	0.80	13.6	13.6	0.88	13.3	13.3	0.95	13.0	13.0	1.11	12.8	12.8	1.29	
	80	67	17.3	14.4	0.38	16.2	13.9	0.52	15.2	13.4	0.66	14.1	12.9	0.80	13.6	12.6	0.87	13.1	12.3	0.94	12.1	11.7	1.08	11.0	11.0	1.21	
Minimum	80	72	17.8	11.0	0.41	17.0	10.7	0.51	15.9	10.3	0.63	14.9	9.8	0.78	14.6	9.7	0.86	14.2	9.5	0.93	13.8	9.3	1.10	13.7	9.0	1.29	
	75	62	14.8	13.9	0.46	13.8	13.5	0.57	13.0	13.0	0.68	12.4	12.4	0.82	12.1	12.1	0.89	11.9	11.9	0.96	11.6	11.6	1.12	11.4	11.4	1.29	
	80	62	24.9	23.7	0.91	23.7	23.0	1.08	22.5	22.5	1.26	21.5	21.5	1.46	20.9	20.9	1.57	20.4	20.4	1.68	19.2	19.2	1.92	17.6	17.6	2.18	
Intermediate	80	67	27.1	19.9	0.91	25.7	19.0	1.07	24.3	18.4	1.25	22.9	17.9	1.45	22.2	17.6	1.56	21.4	17.3	1.68	20.0	16.6	1.93	18.4	15.7	2.20	
	80	72	29.3	15.8	0.80	27.6	15.3	0.99	26.2	14.7	1.20	24.7	14.2	1.43	24.0	13.9	1.54	23.1	13.5	1.64	21.4	12.8	1.91	19.4	11.9	2.17	
	75	62	23.7	19.2	0.91	22.6	18.6	1.08	21.4	18.1	1.26	20.2	17.5	1.47	19.6	17.2	1.57	19.0	17.0	1.69	17.7	16.3	1.92	16.2	15.4	2.18	
Nominal	80	62	37.6	31.7	1.76	35.9	30.8	2.02	34.3	30.0	2.30	32.5	29.2	2.59	31.5	28.5	2.73	30.3	27.8	2.89	28.2	26.8	3.19	25.9	25.6	3.51	
	80	67	38.4	24.9	1.73	37.5	24.9	2.00	36.2	24.5	2.29	34.6	23.8	2.59	33.6	23.4	2.75	32.5	22.9	2.92	30.1	21.9	3.26	27.2	21.1	3.63	
	80	72	44.2	22.1	1.71	42.1	21.3	2.00	40.2	20.5	2.29	38.0	19.7	2.61	36.9	19.3	2.77	35.6	18.8	2.93	32.9	17.8	3.25	29.9	16.7	3.59	
Maximum	75	62	35.9	26.3	1.76	34.5	25.6	2.03	32.9	24.9	2.30	31.2	24.0	2.60	30.2	23.5	2.75	29.2	23.1	2.90	27.506	22.222	3.24	24.9	20.7	3.52	
	80	62	43.2	37.0	2.28	41.3	36.0	2.59	39.3	35.0	2.93	37.3	34.1	3.27	36.1	33.4	3.45	34.8	32.7	3.61	32.6	31.7	3.97	30.0	30.0	4.35	
	80	67	45.5	32.3	2.33	44.0	30.5	2.63	42.2	29.2	2.95	40.2	28.2	3.29	39.1	27.7	3.48	37.9	27.3	3.66	35.4	26.2	4.06	32.7	24.9	4.47	
Speed	Indoor Tdb - in Twb - in																										
	80	72	51.4	26.0	2.24	49.1	25.1	2.58	46.6	24.1	2.96	44.0	23.1	3.33	42.4	22.6	3.51	41.0	22.0	3.69	37.7	20.7	4.07	34.1	19.5	4.46	
	75	62	41.1	30.4	2.28	39.5	29.4	2.59	37.6	28.5	2.94	35.6	27.6	3.28	34.5	27.1	3.46	33.4	26.5	3.63	31.0	25.4	3.99	28.4	24.2	4.36	

Note: Capacity and Sensible Capacity are shown in units of thousands of Btu/h.

## HEATING

Outdoor Temperature:		12°F			17°F			20°F			30°F			40°F			47°F			50°F			60°F				
		Total Capacity	COP	kW	Total Capacity	COP	kW	Total Capacity	COP	kW	Total Capacity	COP	kW	Total Capacity	COP	kW	Total Capacity	COP	kW	Total Capacity	COP	kW	Total Capacity	COP	kW		
Speed	Indoor Tdb - in Twb - in																										
	60	6.3	2.97	0.62	7.1	3.26	0.64	7.4	3.36	0.64	9.1	4.04	0.66	10.7	4.78	0.66	12.1	5.45	0.65	12.6	5.75	0.64	14.7	7.01	0.62		
	70	6.0	2.48	0.71	6.7	2.70	0.72	7.1	2.85	0.73	8.6	3.39	0.74	10.2	4.04	0.74	11.5	4.59	0.73	12.0	4.86	0.73	14.0	5.89	0.70		
Minimum	80	5.8	2.11	0.80	6.4	2.28	0.83	6.8	2.38	0.83	8.3	2.86	0.85	9.8	3.36	0.85	11.0	3.85	0.83	11.5	4.08	0.83	13.5	4.96	0.80		
	60	11.1	2.87	1.13	12.1	3.06	1.15	12.7	3.18	1.17	15.0	3.67	1.19	17.5	4.19	1.22	19.5	4.61	1.24	20.3	4.76	1.25	23.4	5.42	1.26		
	70	10.8	2.51	1.26	11.8	2.68	1.29	12.4	2.79	1.30	14.6	3.19	1.34	17.0	3.65	1.37	18.9	4.01	1.38	19.8	4.17	1.39	22.8	4.75	1.41		
Intermediate	80	10.6	2.21	1.40	11.5	2.35	1.43	12.1	2.44	1.45	14.3	2.81	1.49	16.7	3.23	1.52	18.5	3.54	1.53	19.4	3.66	1.55	22.3	4.19	1.56		
	60	20.8	2.90	2.11	22.8	3.06	2.18	24.0	3.16	2.23	28.0	3.44	2.39	32.0	3.68	2.55	34.9	3.85	2.66	36.1	3.90	2.71	40.1	4.10	2.87		
	70	20.2	2.55	2.32	22.2	2.70	2.41	23.4	2.78	2.46	27.3	3.04	2.64	31.2	3.26	2.81	34.0	3.40	2.93	35.2	3.46	2.98	39.1	3.63	3.16		
Nominal	80	19.8	2.29	2.54	21.7	2.42	2.62	22.9	2.50	2.68	26.7	2.73	2.87	30.6	2.94	3.06	33.3	3.07	3.18	34.4	3.10	3.25	38.3	3.27	3.44		
	60	25.2	2.63	2.80	27.4	2.78	2.88	28.7	2.87	2.93	33.1	3.13	3.10	37.4	3.38	3.25	40.4	3.52	3.36	41.6	3.59	3.40	45.8	3.80	3.53		
	70	24.9	2.42	3.01	27.1	2.55	3.11	28.4	2.63	3.16	32.7	2.87	3.34	36.9	3.08	3.51	39.9	3.23	3.62	41.1	3.29	3.67	45.3	3.48	3.81		
Maximum	80	24.3	2.16	3.28	26.5	2.29	3.38	27.7	2.36	3.44	32.0	2.58	3.64	36.1	2.78	3.81	39.0	2.90	3.93	40.2	2.95	3.99	44.3	3.13	4.14		

# EXPANDED RATINGS - 4 TON WITH G7 FURNACE C CABINET

## COOLING

Outdoor Temperature:		60°F			70°F			80°F			90°F			95°F			100°F			110°F			120°F			
Speed	Indoor Tdb - in	Total Capacity	Sensible Capacity	kW	Total Capacity	Sensible Capacity	kW	Total Capacity	Sensible Capacity	kW	Total Capacity	Sensible Capacity	kW	Total Capacity	Sensible Capacity	kW	Total Capacity	Sensible Capacity	kW	Total Capacity	Sensible Capacity	kW				
Minimum	80	62	16.9	16.9	0.40	16.0	16.0	0.51	15.1	15.1	0.62	14.3	14.3	0.76	14.0	14.0	0.84	13.7	13.7	0.91	13.3	13.3	1.06	13.1	13.1	1.26
	80	67	18.2	13.7	0.34	16.9	13.5	0.48	15.7	13.2	0.62	14.6	12.8	0.76	14.1	12.6	0.84	13.5	12.4	0.91	12.5	11.9	1.06	11.5	11.0	1.22
	80	72	18.0	11.5	0.37	17.5	11.3	0.47	16.3	10.8	0.60	15.3	10.5	0.74	14.9	10.3	0.82	14.5	10.2	0.90	14.0	10.0	1.05	13.7	9.8	1.25
Intermediate	75	62	15.3	15.0	0.42	14.3	14.3	0.53	13.5	13.5	0.66	12.8	12.8	0.78	12.5	12.5	0.86	12.3	12.3	0.93	12.0	12.0	1.07	11.8	11.8	1.26
	80	62	31.0	30.8	1.09	29.7	29.7	1.28	28.4	28.4	1.48	27.1	27.1	1.69	26.4	26.4	1.80	25.6	25.6	1.91	23.8	23.8	2.15	21.9	21.9	2.39
	80	67	32.3	23.6	1.00	31.2	23.1	1.22	29.8	22.6	1.45	28.3	22.0	1.68	27.4	21.7	1.80	26.5	21.4	1.92	24.6	20.5	2.17	22.4	19.5	2.42
Nominal	80	72	35.9	20.1	1.01	34.2	19.4	1.22	32.3	18.8	1.44	30.6	18.1	1.67	29.6	17.7	1.79	28.4	17.2	1.90	26.1	16.2	2.15	23.5	15.2	2.39
	75	62	29.4	24.9	1.09	28.0	24.2	1.28	26.6	23.4	1.49	25.0	22.7	1.70	24.2	22.3	1.81	23.4	21.8	1.92	21.7	20.9	2.15	19.8	19.8	2.38
	80	62	47.3	43.4	2.64	45.4	42.3	2.96	43.4	41.4	3.29	41.3	40.3	3.64	40.2	39.8	3.83	39.2	39.1	4.01	37.3	37.3	4.40	35.3	35.3	4.78
Maximum	80	67	50.9	38.8	2.64	48.9	37.8	2.96	46.6	36.8	3.30	44.3	35.8	3.67	43.0	35.3	3.87	41.7	34.8	4.08	39.0	33.8	4.52	36.6	32.9	4.99
	80	72	55.9	29.4	2.62	53.0	28.4	2.97	50.2	27.3	3.36	47.6	26.4	3.73	46.4	25.9	3.92	45.2	25.4	4.10	42.9	24.5	4.47	40.4	23.6	4.82
	75	62	45.3	35.2	2.65	43.4	34.2	2.96	41.4	33.2	3.30	39.3	32.2	3.66	38.2	31.7	3.84	37.1	31.1	4.03	34.9	30.0	4.40	32.6	28.8	4.78
Maximum	80	62	55.6	50.8	3.44	53.5	49.9	3.79	51.6	48.8	4.19	49.5	47.7	4.62	48.4	47.2	4.85	47.3	46.5	5.07	45.2	45.0	5.53	43.2	43.2	6.01
	80	67	60.3	45.6	3.46	57.8	44.5	3.85	55.5	43.4	4.27	53.1	42.3	4.71	52.0	41.8	4.93	50.9	41.2	5.16	48.5	40.1	5.60	46.1	39.0	6.05
	80	72	65.4	34.2	3.49	62.6	33.1	3.91	60.0	32.2	4.35	57.6	31.3	4.80	56.4	30.9	5.01	55.3	30.4	5.23	53.0	29.7	5.68	50.6	28.8	6.10
75	62	53.2	41.2	3.45	51.3	40.2	3.81	49.3	39.2	4.22	47.2	38.2	4.64	46.1	37.6	4.87	45.0	37.1	5.09	42.7	35.9	5.54	40.4	34.7	6.01	

Note: Capacity and Sensible Capacity are shown in units of thousands of Btu/h.

## HEATING

Outdoor Temperature:		12°F			17°			20°			30°			40°			47°			50°			60°		
Speed	Indoor Tdb - °F	Total Capacity	COP	kW	Total Capacity	COP	kW	Total Capacity	COP	kW	Total Capacity	COP	kW	Total Capacity	COP	kW	Total Capacity	COP	kW	Total Capacity	COP	kW			
Minimum	60	5.6	2.70	0.61	6.3	2.99	0.62	6.8	3.22	0.62	8.4	4.13	0.60	10.1	4.63	0.64	11.2	5.24	0.63	11.8	5.56	0.62	13.6	6.67	0.59
	70	5.4	2.23	0.71	6.1	2.48	0.72	6.5	2.63	0.73	8.0	3.18	0.74	9.6	3.81	0.74	10.8	4.31	0.73	11.3	4.55	0.73	13.0	5.46	0.70
	80	5.1	1.84	0.82	5.8	2.03	0.84	6.3	2.19	0.84	7.8	2.81	0.81	9.3	3.20	0.85	10.4	3.60	0.85	10.9	3.81	0.84	12.5	4.54	0.81
Intermediate	60	14.1	3.33	1.24	15.2	3.53	1.27	16.0	3.65	1.28	18.5	4.14	1.31	21.3	4.62	1.35	23.4	5.05	1.36	24.2	5.22	1.36	27.3	5.85	1.37
	70	13.6	2.85	1.40	14.8	3.03	1.43	15.5	3.15	1.44	17.9	3.55	1.48	20.6	4.00	1.51	22.6	4.34	1.52	23.4	4.49	1.53	26.5	5.04	1.54
	80	13.3	2.50	1.56	14.4	2.64	1.59	15.1	2.75	1.61	17.5	3.12	1.65	20.1	3.49	1.69	22.1	3.80	1.70	22.8	3.92	1.71	25.9	4.42	1.72
Nominal	60	27.2	2.67	2.99	30.3	2.87	3.09	32.1	2.98	3.16	37.9	3.33	3.33	43.1	3.60	3.51	46.5	3.76	3.62	47.8	3.81	3.67	52.1	4.02	3.80
	70	26.9	2.41	3.27	30.0	2.60	3.38	31.8	2.70	3.45	37.5	3.01	3.65	42.7	3.25	3.84	46.0	3.40	3.96	47.4	3.46	4.01	51.5	3.62	4.17
	80	26.3	2.15	3.58	29.3	2.32	3.70	31.1	2.41	3.78	36.6	2.69	3.99	41.7	2.90	4.21	44.9	3.03	4.35	46.2	3.08	4.40	50.3	3.23	4.56
Maximum	60	30.1	2.59	3.41	32.7	2.75	3.49	34.1	2.84	3.53	39.2	3.14	3.66	44.1	3.41	3.79	47.3	3.58	3.87	48.8	3.65	3.92	53.4	3.89	4.02
	70	30.0	2.42	3.64	32.6	2.57	3.72	34.1	2.65	3.77	39.1	2.93	3.92	44.0	3.18	4.05	47.3	3.35	4.14	48.7	3.41	4.18	53.3	3.64	4.30
	80	29.6	2.21	3.93	32.2	2.35	4.02	33.6	2.43	4.05	38.6	2.68	4.22	43.4	2.91	4.37	46.6	3.06	4.46	48.0	3.12	4.51	52.6	3.33	4.64

# EXPANDED RATINGS - 2 TON IQ HEAT PUMP WITH B6VMAI AIR HANDLER

## COOLING

Outdoor Temperature: Speed	60°F			70°F			80°F			90°F			95°F			100°F			110°F			120°F			
	Total Capacity	Sensible Capacity	kW	Total Capacity	Sensible Capacity	kW	Total Capacity	Sensible Capacity	kW	Total Capacity	Sensible Capacity	kW	Total Capacity	Sensible Capacity	kW	Total Capacity	Sensible Capacity	kW	Total Capacity	Sensible Capacity	kW	Total Capacity	Sensible Capacity	kW	
80	62	13.5	13.5	0.34	12.9	12.9	0.41	12.2	12.2	0.50	11.5	11.5	0.61	11.1	11.1	0.68	10.7	10.7	0.74	9.8	9.8	0.88	8.8	8.8	1.03
80	67	14.2	10.9	0.33	13.4	10.5	0.41	12.6	10.0	0.51	11.8	9.7	0.62	11.3	9.5	0.67	10.9	9.3	0.73	10.0	8.9	0.85	9.1	8.5	0.98
80	72	15.2	9.0	0.29	14.8	8.8	0.36	13.8	8.4	0.47	12.8	8.0	0.58	12.2	7.8	0.65	11.7	7.5	0.71	10.5	7.0	0.86	9.3	6.4	1.01
75	62	12.7	11.4	0.34	12.0	11.1	0.41	11.2	10.7	0.51	10.5	10.2	0.62	10.1	10.0	0.68	9.6	9.6	0.75	8.8	8.8	0.89	7.9	7.9	1.04
80	62	17.5	17.5	0.52	16.8	16.8	0.61	16.0	16.0	0.71	15.2	15.2	0.84	14.7	14.7	0.92	14.3	14.3	0.99	13.3	13.3	1.17	12.2	12.2	1.37
80	67	18.9	13.8	0.46	17.9	13.3	0.57	16.9	12.9	0.70	15.9	12.5	0.83	15.4	12.2	0.90	14.8	12.0	0.98	13.7	11.6	1.13	12.6	11.1	1.29
80	72	20.3	11.4	0.48	19.4	11.1	0.56	18.4	10.7	0.67	17.2	10.2	0.81	16.6	10.0	0.89	16.0	9.7	0.97	14.6	9.1	1.16	13.1	8.4	1.38
75	62	16.7	14.3	0.51	15.9	13.9	0.60	15.0	13.5	0.71	14.1	13.0	0.83	13.7	12.7	0.91	13.2	12.5	0.98	12.2	11.9	1.15	11.1	11.1	1.34
80	62	25.4	24.4	0.97	24.3	23.9	1.14	23.3	23.3	1.32	22.3	22.3	1.50	21.7	21.7	1.59	21.1	21.1	1.69	19.8	19.8	1.87	18.4	18.4	2.06
80	67	27.6	18.6	0.94	26.4	18.5	1.11	25.1	18.2	1.28	23.7	17.7	1.47	23.0	17.5	1.57	22.3	17.2	1.68	20.8	16.4	1.90	19.2	15.5	2.13
80	72	29.9	16.4	0.95	28.6	15.9	1.12	27.1	15.4	1.29	25.6	14.8	1.47	24.7	14.5	1.56	23.9	14.2	1.64	22.0	13.4	1.82	20.0	12.6	1.99
75	62	24.5	19.9	0.96	23.5	19.5	1.12	22.3	18.9	1.30	21.1	18.4	1.48	20.5	18.1	1.57	19.8	17.8	1.67	18.4	17.1	1.85	16.9	16.3	2.05
80	62	30.5	28.3	1.31	29.1	27.6	1.51	27.7	27.0	1.73	26.3	26.2	1.96	25.6	25.6	2.08	25.0	25.0	2.19	23.5	23.5	2.43	21.8	21.8	2.65
80	67	32.5	22.9	1.33	31.2	22.4	1.52	29.7	21.8	1.73	28.2	21.2	1.95	27.4	20.9	2.07	26.6	20.6	2.20	24.8	19.8	2.46	23.0	19.0	2.73
80	72	35.9	19.1	1.28	34.3	18.5	1.49	32.6	17.9	1.71	30.6	17.2	1.94	29.6	16.8	2.05	28.6	16.4	2.16	26.4	15.6	2.37	24.0	14.6	2.57
75	62	29.4	23.2	1.29	28.1	22.5	1.49	26.7	21.8	1.70	25.2	21.1	1.93	24.5	20.8	2.05	23.7	20.4	2.16	22.0	19.7	2.40	20.2	18.8	2.63

Note: Capacity and Sensible Capacity are shown in units of thousands of Btu/h.

## HEATING

Outdoor Temperature: Speed	12°F			17°			20°			30°			40°			47°			50°			60°		
	Total Capacity	COP	kW	Total Capacity	COP	kW	Total Capacity	COP	kW	Total Capacity	COP	kW	Total Capacity	COP	kW	Total Capacity	COP	kW	Total Capacity	COP	kW	Total Capacity	COP	kW
60	2.5	2.14	0.34	3.1	2.64	0.34	3.5	2.95	0.34	4.7	4.00	0.34	5.9	5.14	0.34	6.8	6.03	0.33	7.2	6.44	0.33	8.4	8.00	0.31
70	2.3	1.74	0.40	2.9	2.16	0.40	3.3	2.41	0.40	4.5	3.26	0.40	5.6	4.20	0.39	6.5	4.92	0.39	6.8	5.26	0.38	8.0	6.53	0.36
80	2.2	1.40	0.47	2.8	1.73	0.47	3.1	1.93	0.47	4.2	2.62	0.47	5.4	3.37	0.47	6.1	3.95	0.46	6.5	4.22	0.45	7.6	5.24	0.43
60	6.9	3.29	0.61	7.7	3.59	0.63	8.1	3.77	0.63	9.8	4.39	0.65	11.4	5.07	0.66	12.6	5.59	0.66	13.1	5.82	0.66	14.9	6.69	0.65
70	6.6	2.72	0.71	7.4	2.96	0.73	7.8	3.11	0.74	9.4	3.62	0.76	11.0	4.18	0.77	12.1	4.61	0.77	12.6	4.81	0.77	14.3	5.52	0.76
80	6.4	2.28	0.82	7.1	2.48	0.84	7.5	2.60	0.85	9.0	3.03	0.87	10.5	3.50	0.88	11.6	3.86	0.88	12.1	4.03	0.88	13.7	4.62	0.87
60	13.6	3.04	1.31	14.9	3.26	1.34	15.7	3.40	1.36	18.5	3.84	1.41	21.3	4.26	1.47	23.3	4.56	1.50	24.2	4.69	1.51	27.1	5.11	1.56
70	13.1	2.62	1.47	14.0	2.73	1.50	15.2	2.93	1.52	17.9	3.31	1.59	20.6	3.68	1.64	22.6	3.93	1.68	23.4	4.04	1.70	26.2	4.40	1.75
80	12.7	2.26	1.65	14.0	2.43	1.69	14.7	2.53	1.71	17.3	2.85	1.78	20.0	3.17	1.84	21.8	3.39	1.89	22.7	3.49	1.90	25.4	3.80	1.96
60	14.8	2.94	1.48	16.2	3.16	1.51	17.1	3.29	1.52	19.9	3.73	1.57	22.9	4.16	1.61	25.0	4.46	1.64	26.0	4.59	1.66	29.1	5.02	1.70
70	14.3	2.55	1.64	15.6	2.74	1.67	16.4	2.85	1.69	19.2	3.23	1.74	22.1	3.61	1.79	24.1	3.87	1.82	25.0	3.99	1.84	28.0	4.36	1.88
80	13.7	2.21	1.82	15.0	2.38	1.85	15.8	2.48	1.87	18.5	2.81	1.93	21.2	3.14	1.98	23.2	3.36	2.02	24.0	3.46	2.03	26.9	3.79	2.08



# EXPANDED RATINGS - 3 TON IQ HEAT PUMP WITH B6VMAI AIR HANDLER

## COOLING

Outdoor Temperature:	60°F			70°F			80°F			90°F			95°F			100°F			110°F			120°F				
	Indoor Tdb - in	Indoor Twb - in	Speed	Total Capacity	Sensible Capacity	kW	Total Capacity	Sensible Capacity	kW	Total Capacity	Sensible Capacity	kW	Total Capacity	Sensible Capacity	kW	Total Capacity	Sensible Capacity	kW	Total Capacity	Sensible Capacity	kW	Total Capacity	Sensible Capacity	kW		
Minimum	80	62	16.9	16.0	16.0	0.54	15.1	15.1	0.65	14.4	14.4	0.78	14.1	14.1	0.86	13.8	13.8	0.93	13.5	13.5	1.09	13.3	13.3	1.26		
	80	67	18.0	16.9	13.6	0.51	15.8	13.1	0.65	14.7	12.6	0.78	14.2	12.3	0.85	13.6	12.0	0.92	12.5	11.4	1.05	11.5	10.8	1.19		
	80	72	18.5	11.4	0.40	17.7	11.1	0.50	16.5	10.2	0.76	15.2	10.1	0.84	14.8	9.9	0.91	14.4	9.7	1.08	14.2	9.4	1.26			
Intermediate	75	62	15.4	14.5	0.45	14.4	14.0	0.56	13.5	12.9	0.80	12.6	12.6	0.87	12.4	12.4	0.94	12.0	12.0	1.10	11.9	11.9	1.26			
	80	62	25.9	24.6	0.86	24.6	23.9	1.02	23.4	22.3	1.38	21.7	21.7	1.49	21.2	21.2	1.59	19.9	19.9	1.82	18.3	18.3	2.06			
	80	67	28.1	19.8	0.86	26.7	18.9	1.01	25.3	18.3	1.18	17.8	17.8	1.37	17.5	1.48	22.3	17.2	1.59	20.7	16.6	1.82	19.2	15.6	2.08	
Nominal	80	72	30.4	16.4	0.76	28.7	15.9	0.94	27.2	15.3	1.14	14.7	14.7	1.35	24.9	14.4	1.46	24.0	14.0	1.56	22.2	13.3	1.81	20.2	12.4	2.05
	75	62	24.6	19.9	0.86	23.5	19.3	1.02	22.3	18.8	1.19	21.0	18.2	1.39	20.3	17.9	1.49	19.7	17.6	1.60	18.4	16.9	1.82	16.0	2.06	
	80	62	39.2	33.0	1.72	37.4	32.1	1.97	35.7	31.2	2.25	30.4	25.3	32.8	29.7	2.67	31.6	29.0	2.82	29.4	27.9	3.12	27.0	26.7	3.43	
Maximum	80	67	39.9	24.9	1.69	39.1	24.9	1.95	37.7	24.5	2.23	36.0	23.8	2.53	35.0	23.4	2.69	33.9	22.9	2.85	31.3	21.9	3.19	28.3	21.1	3.54
	80	72	46.0	23.0	1.67	43.9	22.2	1.95	41.9	21.4	2.24	39.6	20.5	2.55	38.4	20.1	2.71	37.1	19.6	2.86	34.3	18.5	3.18	31.1	17.4	3.51
	75	62	37.4	27.4	1.72	35.9	26.7	1.98	34.3	25.9	2.25	32.5	25.0	2.54	31.5	24.5	2.69	30.5	24.0	2.83	28.652	23.124	3.17	25.9	21.5	3.44
Maximum	80	62	45.0	38.5	2.23	43.0	37.5	2.53	40.9	36.5	2.86	38.9	35.5	3.20	37.6	34.8	3.37	36.2	34.1	3.53	34.0	33.0	3.88	31.3	31.3	4.25
	80	67	47.4	32.3	2.28	45.8	30.5	2.57	43.9	29.2	2.88	41.8	28.2	3.22	40.7	27.8	3.40	39.5	27.3	3.58	36.9	26.2	3.96	34.0	24.9	4.37
	80	72	53.5	27.1	2.19	51.1	26.1	2.52	48.5	25.1	2.89	45.8	24.1	3.25	44.2	23.5	3.43	42.7	22.9	3.61	39.3	21.6	3.98	35.5	20.3	4.36
75	62	42.9	31.6	2.23	41.1	30.6	2.53	39.2	29.7	2.87	37.1	28.7	3.21	35.9	28.1	3.38	34.8	27.6	3.55	32.3	26.4	3.90	29.6	25.1	4.26	

Note: Capacity and Sensible Capacity are shown in units of thousands of Btu/h.

## HEATING

Outdoor Temperature:	12°F			17°			20°			30°			40°			47°			50°			60°			
	Indoor Tdb - °F	Total Capacity	COP	kW	Total Capacity	COP	kW	Total Capacity	COP	kW	Total Capacity	COP	kW	Total Capacity	COP	kW	Total Capacity	COP	kW	Total Capacity	COP	kW			
Minimum	60	6.0	2.98	0.59	6.8	3.29	0.60	7.2	3.48	0.61	8.9	4.15	0.63	10.6	4.91	0.63	11.9	5.52	0.63	12.4	5.80	0.63	14.3	6.86	0.61
	70	5.7	2.51	0.67	6.4	2.76	0.68	6.9	2.92	0.69	8.4	3.49	0.71	10.1	4.13	0.71	11.3	4.64	0.71	11.8	4.87	0.71	13.6	5.76	0.69
	80	5.5	2.11	0.76	6.2	2.33	0.78	6.6	2.46	0.79	8.1	2.94	0.81	9.7	3.48	0.82	10.8	3.90	0.81	11.3	4.10	0.81	13.1	4.85	0.79
Intermediate	60	11.1	2.91	1.12	12.1	3.11	1.14	12.7	3.24	1.15	15.0	3.71	1.18	17.5	4.24	1.21	19.5	4.65	1.23	20.3	4.84	1.23	23.4	5.51	1.25
	70	10.8	2.54	1.25	11.8	2.71	1.27	12.4	2.82	1.28	14.6	3.23	1.32	17.0	3.70	1.35	18.9	4.06	1.37	19.8	4.22	1.37	22.8	4.81	1.39
	80	10.6	2.23	1.39	11.5	2.39	1.41	12.1	2.49	1.43	14.3	2.85	1.47	16.7	3.25	1.50	18.5	3.57	1.52	19.4	3.71	1.53	22.3	4.23	1.54
Nominal	60	20.4	2.76	2.16	22.6	2.95	2.24	23.9	3.06	2.28	28.1	3.39	2.42	32.1	3.69	2.55	34.9	3.89	2.63	36.0	3.96	2.66	39.7	4.22	2.76
	70	19.8	2.44	2.38	22.0	2.61	2.47	23.3	2.71	2.52	27.4	3.01	2.67	31.3	3.27	2.81	34.0	3.44	2.90	35.1	3.51	2.93	38.7	3.74	3.04
	80	19.4	2.19	2.60	21.5	2.35	2.69	22.8	2.43	2.74	26.8	2.70	2.91	30.7	2.94	3.06	33.3	3.09	3.15	34.3	3.15	3.19	37.9	3.35	3.31
Maximum	60	25.2	2.67	2.76	27.4	2.82	2.85	28.7	2.90	2.90	33.1	3.17	3.06	37.4	3.41	3.21	40.4	3.57	3.32	41.6	3.63	3.36	45.8	3.84	3.49
	70	24.9	2.45	2.97	27.1	2.58	3.07	28.4	2.66	3.13	32.7	2.90	3.30	36.9	3.12	3.47	39.9	3.27	3.58	41.1	3.33	3.62	45.3	3.52	3.77
	80	24.3	2.20	3.24	26.5	2.32	3.34	27.7	2.39	3.40	32.0	2.61	3.59	36.1	2.80	3.77	39.0	2.94	3.89	40.2	2.99	3.94	44.3	3.17	4.10

# EXPANDED RATINGS - 4 TON IQ HEAT PUMP WITH B6VMAI AIR HANDLER

## COOLING

Outdoor Temperature: Speed	60°F			70°F			80°F			90°F			95°F			100°F			110°F			120°F			
	Indoor Tdb - in	Total Capacity	Sensible Capacity	Indoor Tdb - in	Total Capacity	Sensible Capacity	Indoor Tdb - in	Total Capacity	Sensible Capacity	Indoor Tdb - in	Total Capacity	Sensible Capacity	Indoor Tdb - in	Total Capacity	Sensible Capacity	Indoor Tdb - in	Total Capacity	Sensible Capacity	Indoor Tdb - in	Total Capacity	Sensible Capacity	Indoor Tdb - in	Total Capacity	Sensible Capacity	
Minimum	80	62	17.2	17.2	0.38	16.3	0.48	15.4	0.59	14.6	0.72	14.3	0.79	14.0	0.86	13.6	0.99	13.6	1.00	13.6	1.00	13.4	1.00	13.4	1.19
	80	67	18.5	14.6	0.32	17.3	0.45	16.1	0.58	14.9	0.72	14.3	0.79	13.8	0.86	12.7	1.00	12.7	1.00	12.7	1.00	11.7	1.00	11.7	1.15
	80	72	18.3	11.7	0.35	17.8	0.44	16.6	0.57	15.6	0.70	15.2	0.77	14.8	0.85	14.3	0.99	14.3	1.02	0.99	14.0	1.00	14.0	1.18	
Intermediate	75	62	15.6	15.2	0.40	14.6	0.50	13.7	0.62	13.1	0.74	12.8	0.81	12.6	0.88	12.2	1.01	12.2	1.01	12.2	1.01	12.0	1.01	12.0	1.19
	80	62	30.2	30.0	1.08	28.9	1.27	27.7	1.47	26.4	1.68	25.7	1.79	24.9	1.90	23.2	2.13	23.2	2.13	2.13	21.3	2.13	21.3	2.37	
	80	67	31.5	23.3	0.99	30.3	1.21	29.0	1.43	27.5	1.67	26.7	1.79	25.8	1.91	23.9	2.15	23.9	2.15	2.15	21.8	2.15	21.8	2.40	
Nominal	80	72	35.0	19.6	1.00	33.3	1.21	31.5	1.43	29.8	1.66	28.8	1.78	27.7	1.89	25.4	2.13	25.4	2.13	2.13	22.9	2.13	22.9	2.37	
	75	62	28.6	24.3	1.08	27.3	1.27	25.9	1.48	24.4	1.69	23.6	1.78	22.8	1.91	21.1	2.04	21.1	2.04	2.04	19.3	2.04	19.3	2.36	
	80	62	49.0	44.9	1.43	47.0	1.62	45.6	1.84	44.2	2.06	43.2	2.28	42.7	2.51	40.4	2.75	40.4	2.75	40.4	2.75	37.5	2.75	37.5	4.39
Maximum	80	67	52.7	37.3	1.43	50.6	1.72	48.2	2.06	46.8	2.39	45.8	2.61	44.7	2.84	42.7	3.19	42.7	3.19	42.7	3.19	41.8	3.19	41.8	4.43
	80	72	57.8	30.4	1.41	54.9	1.73	52.0	2.06	49.3	2.39	48.0	2.61	46.8	2.84	44.7	3.19	44.7	3.19	44.7	3.19	41.8	3.19	41.8	4.43
	75	62	46.8	36.4	1.44	44.9	1.73	42.8	2.06	40.7	2.39	39.6	2.61	38.4	2.84	36.1	3.19	36.1	3.19	36.1	3.19	33.7	3.19	33.7	4.39
Maximum	80	62	57.5	52.6	1.46	55.4	1.73	53.4	2.06	51.2	2.39	50.1	2.61	48.8	2.84	46.8	3.19	46.8	3.19	46.8	3.19	44.7	3.19	44.7	6.05
	80	67	62.4	43.8	1.48	59.9	1.73	57.4	2.06	55.0	2.39	53.8	2.61	52.7	2.84	50.2	3.19	50.2	3.19	50.2	3.19	47.7	3.19	47.7	6.09
	80	72	67.7	35.4	1.51	64.8	1.73	62.1	2.06	59.6	2.39	58.4	2.61	57.2	2.84	54.8	3.19	54.8	3.19	54.8	3.19	52.4	3.19	52.4	6.14
75	62	55.1	42.6	1.47	53.1	1.73	51.0	2.06	48.8	2.39	47.7	2.61	46.6	2.84	44.2	3.19	44.2	3.19	44.2	3.19	41.8	3.19	41.8	6.05	

Note: Capacity and Sensible Capacity are shown in units of thousands of Btu/h.

## HEATING

Outdoor Temperature: Speed	12°F			17°			20°			30°			40°			47°			50°			60°		
	Indoor Tdb - °F	Total Capacity	COP	Indoor Tdb - °F	Total Capacity	COP	Indoor Tdb - °F	Total Capacity	COP	Indoor Tdb - °F	Total Capacity	COP	Indoor Tdb - °F	Total Capacity	COP	Indoor Tdb - °F	Total Capacity	COP	Indoor Tdb - °F	Total Capacity	COP	Indoor Tdb - °F	Total Capacity	COP
Minimum	60	7.0	3.66	0.56	7.6	3.95	0.56	7.9	4.13	0.56	9.3	4.83	0.56	10.8	5.66	11.9	6.34	0.55	12.5	6.65	14.3	7.84	0.53	
	70	6.7	3.01	0.65	7.3	3.25	0.65	7.6	3.40	0.66	8.9	3.97	0.70	10.3	4.66	11.4	5.21	0.64	11.9	5.47	13.7	6.45	0.62	
	80	6.4	2.51	0.75	7.0	2.71	0.76	7.3	2.84	0.76	8.6	3.31	0.76	10.0	3.88	11.0	4.35	0.74	11.5	4.56	13.2	5.38	0.72	
Intermediate	60	14.2	3.52	1.18	15.4	3.75	1.20	16.1	3.89	1.22	18.7	4.39	1.25	21.5	4.94	23.6	5.36	1.29	24.5	5.55	27.6	6.23	1.30	
	70	13.7	3.03	1.33	14.9	3.22	1.35	15.6	3.35	1.37	18.1	3.78	1.41	20.8	4.25	22.8	4.61	1.45	23.7	4.78	26.7	5.36	1.46	
	80	13.4	2.65	1.48	14.5	2.82	1.51	15.2	2.93	1.53	17.7	3.31	1.57	20.3	3.72	22.3	4.04	1.62	23.1	4.18	26.1	4.69	1.63	
Nominal	60	27.2	2.64	3.02	30.3	2.88	3.09	32.1	3.01	3.13	37.9	3.42	3.25	43.1	3.76	46.5	3.98	3.42	47.8	4.07	52.1	4.33	3.52	
	70	26.9	2.38	3.31	30.0	2.60	3.38	31.8	2.72	3.42	37.5	3.09	3.56	42.7	3.40	46.0	3.60	3.74	47.4	3.68	51.5	3.92	3.86	
	80	26.3	2.13	3.62	29.3	2.32	3.70	31.1	2.43	3.75	36.6	2.76	3.89	41.7	3.04	44.9	3.21	4.10	46.2	3.28	41.3	3.49	4.22	
Maximum	60	30.4	2.75	3.24	33.0	2.92	3.31	34.5	3.02	3.35	39.6	3.33	3.48	44.5	3.62	47.8	3.81	3.68	49.3	3.88	53.9	4.14	3.82	
	70	30.3	2.57	3.46	32.9	2.73	3.53	34.5	2.82	3.58	39.5	3.11	3.72	44.4	3.38	47.8	3.56	3.94	49.2	3.63	53.8	3.86	4.08	
	80	29.9	2.35	3.73	32.5	2.50	3.81	34.0	2.58	3.85	39.0	2.85	4.01	43.8	3.10	47.1	3.26	4.24	48.5	3.32	53.1	3.54	4.40	

## ACCESSORIES - CONDENSING UNIT

Controller/Thermostat - 920620\*

\* Revision "D" or later.



**MAYTAG**

Before purchasing this appliance, read important energy cost and efficiency information available from your retailer. Specifications and illustrations subject to change without notice and without incurring obligations.

Manufactured under license by Nortek Global HVAC LLC, O'Fallon, MO. ®Registered Trademark/™ Trademark of Maytag Corporation or its related companies. ©Nortek Global HVAC LLC 2015. All rights reserved.

350D-1212 (Replaces 350D-0212)

Printed in U.S.A. (12/12)