Gibson®

Product Line



96% AFUE Gas Furnaces

All gas furnaces except KG8SA feature SmartLite® Control Boards

KG7TE
96% AFUE Ultra High Efficiency, Direct Vent or Non-Direct Vent, Condensing, 2-Stage, Dedicated, Multi-Speed ECM Blower Motor, 60,000 - 120,000 BTUH Input

KG7TN
96% AFUE Ultra High Efficiency, Direct Vent or Non-Direct Vent, Condensing, 2-Stage, Downflow, Multi-Speed ECM Blower Motor, 60,000 - 120,000 BTUH Input



95.1% AFUE Gas Furnaces

KG7TC
95.1% AFUE Extra High Efficiency, Direct Vent or Non-Direct Vent, Condensing, 2-Stage Upflow/Horizontal, Multi-Speed ECM Blower Motor, 60,000 - 120,000 BTUH Input



95% AFUE Gas Furnaces

KG7SD
95% AFUE High Efficiency, Direct Vent or Non-Direct Vent, Condensing, 1-Stage, Upflow/ Horizontal, Multi-Speed ECM Blower Motor, 38,000 - 120,000, BTUH Input

KG7SM
95% AFUE High Efficiency, Direct Vent or Non-Direct Vent, Condensing, 1-Stage, Downflow, Multi-Speed ECM Blower Motor, 54,000 - 90,000 BTUH Input



92.1% AFUE Gas Furnaces

KG7SC
92.1% AFUE High Efficiency, Direct Vent or Non-Direct Vent, Condensing, 1-Stage, Upflow/Horizontal, Multi-Speed ECM Blower Motor, 38,000 - 120,000 BTUH Input

KG7SL
92.1% AFUE High Efficiency, Direct Vent or Non-Direct Vent, Condensing, 1-Stage, Downflow, Multi-Speed ECM Blower Motor, 72,000 BTUH Input



80% AFUE Gas Furnaces

KG8SA
80% AFUE Ultra-Low NOx, Standard Efficiency, 1-Stage Upflow/ Horizontal, Multi-Speed ECM Blower Motor, 55,000 - 100,000 BTUH Input

KG7TA
80% AFUE Mid Efficiency, 2-Stage, Upflow/ Horizontal, Multi-Speed ECM Blower Motor, 60,000 - 120,000 BTUH Input

KG7TK
80% AFUE Mid Efficiency, 2-Stage, Downflow, Multi-Speed ECM Blower Motor, 60,000 - 120,000 BTUH Input

KG7SA
80% AFUE Standard Efficiency, 1-Stage Upflow/Horizontal, Multi-Speed ECM Blower Motor, 45,000 - 126,000 BTUH Input

KG7SK
80% AFUE Standard Efficiency, 1-Stage Downflow, Multi-Speed ECM Blower Motor, 54,000 - 126,000 BTUH Input



Convertible Airflow Packaged Systems

All packaged systems feature enhanced coil technology

R8GE
Single Packaged Gas/ Electric, SmartLite Control Board, Square Duct Connections, Convertible Airflow, 14 SEER, 81% AFUE, 11 EER, 2 - 5 Ton, 45,000 - 120,000 BTUH Input



P8SE
Single Packaged Air Conditioner, Square Duct Connections, Convertible Airflow, 14 SEER, up to 11.5 EER, 3, 4 and 5 Ton



Q6SE
Single Packaged Heat Pump, Square Duct Connections, Convertible Airflow, 14 SEER, 8.0 HSPF, 11 EER, 2 - 5 Ton



Horizontal Airflow Packaged Systems

P7RE
Single Packaged Air Conditioner, Round Duct Connections, Horizontal Airflow, 14 SEER, 11 EER, 1-1/2 - 5 Ton



Q7RE
Single Packaged Heat Pump, Round Duct Connections, Horizontal Airflow, 14 SEER, 8.0 HSPF, 11 EER, 2 - 5 Ton



Split Systems Air Conditioners

WSA2BF
Extra High Efficiency, 16 SEER, Single-Stage, Air Conditioner, 2 - 5 Ton Capacity

WSA2BE
High Efficiency, Up to 15 SEER, Air Conditioner, Single-Stage, 1-1/2 - 5 Ton Capacity

WSA2BD
High Efficiency, Up to 14 SEER, Single-Stage, Air Conditioner, 1-1/2 - 5 Ton Capacity



Split Systems Heat Pumps

WSH2BF
Extra High Efficiency, 16 SEER, up to 9.0 HSPF, Single-Stage, Heat Pump, 2 - 5 Ton Capacity

WSH2BE
High Efficiency, Up to 15 SEER, up to 8.5 HSPF, Single-Stage, Heat Pump, 1-1/2 - 5 Ton Capacity



Air Handlers

B6VMAX
Multi-Poised, Vertical/ Horizontal, Variable-Speed, Air Handler, TXV

B6VMMX
ECM Variable-Speed Motor, Multi-Poised, Air Handler, TXV

B6BMMX
Multi-Poised, Vertical/ Horizontal, Multi-Speed, Air Handler

B6BMM0
Multi-Speed, Multi-Poised, Air Handler

B6EMMX
ECM Fixed-Speed Motor, Multi-Poised, Air Handler, TXV



Air Handlers continued

B6BW
Vertical Wall Mount, Air Handler

B6EW
Vertical Wall Mount, Multi-Speed, ECM Motor, Air Handler

MB7VM
Modular , Variable-Speed Model (matched with a cased coil easily creates a 2 piece Air Handler)



Indoor Coils

C7B(A, H)M0
A, B, C and D sizes available in various capacities

Cased & Uncased, Vertical/Horizontal Multi-poised versions available

C7B(A, H)MX
Factory-installed TXV, A, B, C and D sizes available in various capacities

Cased & Uncased, Vertical/Horizontal Multi-poised versions available

C6BH-X
A, B, C and D sizes available in various capacities

Cased, Uncased & Horizontal versions available



ENERGY STAR PARTNER

ENERGY STAR® certification is awarded to products designed to reduce energy consumption and utility costs.

Gas furnaces must have an AFUE of 95% or higher for northern states, at least 90% AFUE for southern states, have an approved energy efficient blower motor and cabinet air leakage of less than or equal to 2%.

Split system air conditioners and heat pumps must have a 15.0 SEER rating or higher and an EER of 12.5 or higher. Split system heat pumps must also have an HSPF of 8.5 or higher.

System Accessories

Air Cleaners

Electronic Air Cleaner
Lifetime filtering systems, removes household allergens and pollutants down to .01 microns



Media Air Cleaner
MERV 14, long life media filter, removes airborne particles down to 0.3 microns



1" Electronic Air Cleaner
Easy to maintain, 24V, 95% efficient down to .01 microns



HEPA Air Cleaner
High efficiency air filtration, captures 99.97% of harmful airborne pollutants



Thermostats

Universal, Programmable 7-day, 24V, digital, up to 3 heat/2 cool, backlit display + keypad, auto or manual changeover



UV Air Treatment Systems

UV object purifiers and Photo Catalytic Oxidation (PCO) units remove mold, bacteria, and viruses that are found in the air stream and also remove odors from the home



Humidifiers

Eliminates parched, dry air which can cause dry nose & throat, itchy & dry skin by delivering humidity and reducing static electricity



Mini Split Heat Pump Systems

GXH_(_)KSK4DH
U-Crown, up to 30.5 SEER, 10.5 HSPF, 12K to 18K BTU, Single-Zone, Cold Climate, Mini Split Heat Pump ODU, operation to -22°F, 208/230 Volt, 60 Hz, 1-Phase



GHH_(_)KSK4DH
U-Crown, up to 30.5 SEER, 10.5 HSPF, 12K to 18K BTU, Single-Zone, Cold Climate, Mini Split Wall Mount IDU, operation to -22°F, 208/230 Volt, 60 Hz, 1-Phase



GXH_(_)LSK4DH
Up to 23 SEER, up to 10.5 HSPF, 9K to 36K BTU, Single-Zone, Mini Split Heat Pump ODU, 208/230 Volt, 60 Hz, 1-Phase



GHH_(_)LSK4DH
Up to 23 SEER, up to 10.5 HSPF, 9K to 36K BTU, Single-Zone, Mini Split Wall Mount IDU, 208/230 Volt, 60 Hz, 1-Phase



GXH_(_)LSA4DL
16 SEER, up to 9.0 HSPF, 9K to 36K BTU, Single-Zone, Mini Split Heat Pump ODU, 115 and 208/230 Volt, 60 Hz, 1-Phase



GHH_(_)LSA4DL
16 SEER, up to 9.0 HSPF, 9K to 36K BTU, Single-Zone, Mini Split Wall Mount IDU, 115 and 208/230 Volt, 60 Hz, 1-Phase



10 YEAR WARRANTY Gibson

Gibson split system air conditioners and heat pumps offer a 10-Year limited warranty that covers all parts when registered as part of a complete Gibson system. Air handlers and coils carry a 3-Year all parts limited warranty and when installed with a matched outdoor unit, will carry the outdoor system warranty. All Gibson gas furnaces and packaged systems offer a 10-Year limited warranty that covers all parts when registered. Additionally, Gibson gas furnaces and gas/electric packaged systems carry a limited lifetime warranty on the heat exchanger. To learn more about our product warranties, ask your Gibson contractor.

Gibson ductless mini-split systems offer a 5-Year limited parts warranty, compressors carry a 7-Year warranty.

Flex Match Mini Split Heat Pump Systems

GXH_(_)FMK4DH
Up to 22 SEER, up to 10.2 HSPF, 1 to 5 IDUs, 18K to 42K BTU, Multi-Zone, Mini Split Heat Pump ODU, 208/230 Volt, 60 Hz, 1-Phase




GHH_(_)LUK4DH
Up to 22 SEER, 9K to 24K BTU, Multi-Zone, Mini Split Wall Mount IDU, 208/230 Volt, 60 Hz, 1-Phase



GDH_(_)FMK4DH
Up to 22 SEER, 9K to 24K BTU, Multi-Zone, Mini Split Ducted IDU, 208/230 Volt, 60 Hz, 1-Phase



GKH_(_)FMK4DH
Up to 22 SEER, 9K to 24K BTU, Multi-Zone, Mini Split 4-Way Cassette IDU, 208/230 Volt, 60 Hz, 1-Phase



GCH_(_)FMK4DH
Up to 22 SEER, 9K to 24K BTU, Multi-Zone, Mini Split Console IDU, 208/230 Volt, 60 Hz, 1-Phase



GFH_(_)FMK4DH
Up to 22 SEER, 9K to 24K BTU, Multi-Zone, Mini Split Floor/Ceiling IDU, 208/230 Volt, 60 Hz, 1-Phase



U-Match Mini Split Heat Pump Systems

GXH_(_)USV4DH
Up to 20 SEER, ??? HSPF, 1 to 1 Match, 18K to 48K BTU, Large Capacity Single-Zone, Mini Split Heat Pump ODU, 208/230 Volt, 60 Hz, 1-Phase



GKU_(_)USV4DH
Up to 22 SEER, 9K to 24K BTU, Multi-Zone, Mini Split 4-Way Cassette IDU, 208/230 Volt, 60 Hz, 1-Phase



GDU_(_)USV4DH
Up to 22 SEER, 9K to 24K BTU, Multi-Zone, Mini Split Ducted IDU, 208/230 Volt, 60 Hz, 1-Phase



GFU_(_)USV4DH
Up to 22 SEER, 9K to 24K BTU, Multi-Zone, Mini Split Floor/Ceiling IDU, 208/230 Volt, 60 Hz, 1-Phase



Mini Split Remotes & Controllers

RC
Remote, Wireless, 16 & 23 SEER Single Zone, Wall Mount and WRC-RD Kit for Ducted IUDs



WRC-RD
Wireless Remote Kit for Ducted IUDs



Mini Split Remotes & Controllers continued

WLRC4F
Remote, Wireless, Single Zone, 23 SEER, Flex Match

WLRC3
Remote, Wireless, Flex Match for Ducted, Cassette & Floor/Ceiling IDUs

WLRC6
Remote, Wireless, Flex Match for Console IUDs



WRC3
Controller, Wired, Flex Match for Ducted, Cassette & Floor/Ceiling IDUs



WRC4
Controller, Wired, Single Zone, 23 SEER, Flex Match optional for Wall Mount IDUs



WLRC2
Remote, Wireless, U-Match, standard for Cassette & Floor/Ceiling IDUs, optional for Ducted IUDs



WRC4
Controller, Wired, U-Match, standard for Ducted IUDs, optional for Cassette & Floor/Ceiling IDUs



Gibson®

Specifications and illustrations subject to change without incurring obligation.

www.gibsonhvac.com

Gibson® is a registered trademark used under license from Gibson International Company, U.S.A. SmartLite® is a registered trademark of Nortek Global HVAC, LLC. © Nortek Global HVAC, LLC 2020. All Rights Reserved. Printed in U.S.A.

379F-0220