NuTone® Product Line



All packaged systems feature Anteater® or Anteater MC® Micro-Channel evaporator coils

97+% Gas Furnaces

All gas furnaces feature SmartLite® Control Boards

FG7MQ
97+ AFUE Ultra High Efficiency, Fully Modulating, Condensing, Upflow/Horizontal Gas Furnace, iSEER® technology, iQ Drive® Ready, 60,000 -120,000 BTUH Input, Variable-Speed Blower



95.1% Gas Furnaces

FG7T(C, L)-VS
95.1 AFUE Extra High Efficiency, Direct Vent or Non-Direct Vent, Condensing, 2-Stage (Upflow/Horizontal, Downflow) Gas Furnace, iSEER technology, iQ Drive Ready, 60,000 - 120,000 BTUH Input, Variable-Speed Blower



FG7T(C, L)-FS
95.1 AFUE Extra High Efficiency, Direct Vent or Non-Direct Vent, Condensing, 2-Stage (Upflow/Horizontal, Downflow) Gas Furnace, iSEER ECM Blower technology, 60,000 - 120,000 BTUH Input



95% Gas Furnaces

FG7S(D, M)
95 AFUE Extra High Efficiency, Direct Vent or Non-Direct Vent, Condensing, 1-Stage, (Upflow/Horizontal, Downflow) Gas Furnace, Multi-Speed PSC Blower Motor, (38,000 - 120,000, 54,000 - 118,000) BTUH Input



92.1% Gas Furnaces

FG7S(C, L)
92.1 AFUE Extra High Efficiency, Direct Vent or Non-Direct Vent, Condensing, 1-Stage, (Upflow/Horizontal, Downflow) Gas Furnace, Multi-Speed PSC Blower Motor, (38,000 - 120,000, 54,000 - 120,000) BTUH Input



80% Gas Furnaces

FG7T(A, K)-VS
80 AFUE High Efficiency, 2-Stage (Upflow/Horizontal, Downflow) Gas Furnace, iSEER technology, iQ Drive Ready, 60,000 - 140,000 BTUH Input, Variable-Speed Blower



80% Gas Furnaces

FG7T(A, K)-FS
80 AFUE High Efficiency, 2-Stage (Upflow/Horizontal, Downflow) Gas Furnace, iSEER ECM Blower technology, 60,000 - 140,000 BTUH Input

FG7S(A, K)
80 AFUE High Efficiency, 1-Stage, (Upflow/Horizontal, Downflow) Gas Furnace, Multi-Speed PSC Blower Motor, (45,000 - 126,000, 54,000 - 126,000) BTUH Input



Packaged Systems

All gas/electric and iHybrid® packaged systems feature SmartLite Control Boards



R6GF-B
Single Packaged Gas/Electric, 2-Stage Heat & Cool, Variable-Speed Blower, Square Duct Connections, Convertible Airflow, 15 SEER, 81% AFUE, 12 EER, 2 - 5 Ton, 80,000 - 120,000 BTUH Input

Packaged Systems

R6GI
Ultra High Efficiency, Single Packaged Gas/Electric, iQ Drive Technology, functions with 2-Stage Gas Heat/5-Stage Cooling output from 2-Stage thermostat, Variable-Speed ECM Blower, Square Duct Connections, Convertible Airflow, 20 SEER, 81% AFUE, Up to 13 EER, 2 - 5 Ton, 80,000 - 120,000 BTUH Input



DF6SF-B
Single Packaged iHybrid Dual Fuel, 2-Stage Gas Heat/ 2-Stage Cooling, Variable-Speed Blower, Square Duct Connections, Convertible Airflow, 15 SEER, 8.0 HSPF, 81% AFUE, 12 EER, 2 - 5 Ton, 80,000 - 120,000 BTUH Input



R8HE-A
Single Packaged Gas/ Electric, 2-Stage Heat, Variable-Speed ECM Blower, Square Duct Connections, Convertible Airflow, 14 SEER, 95% AFUE, up to 12 EER, 2 - 5 Ton, 60,000 - 96,000 BTUH Input



R8GE
Single Packaged Gas/ Electric, Square Duct Connections, Convertible Airflow, 14 SEER, 81% AFUE, 11 EER, 2 - 5 Ton, 45,000 - 120,000 BTUH Input



Packaged Systems

P5RF-A
Single Packaged Air Conditioner, 2-Stage, ECM Blower, Round Duct Connections, 15 SEER, 12 EER, 2 - 5 Ton

Q5RF-A
Single Packaged Heat Pump, 2-Stage, ECM Blower, Round Duct Connections, 15 SEER, 8.0 HSPF, 12 EER, 2 - 5 Ton

P8SE
Single Packaged Air Conditioner, Square Duct Connections, Convertible Airflow, 14 SEER, up to 11.5 EER, 3, 4 and 5 Ton

Q6SE
Single Packaged Heat Pump, Square Duct Connections, Convertible Airflow, 14 SEER, 8.0 HSPF, 11 EER, 2 - 5 Ton

P7RE
Single Packaged Air Conditioner, Round Duct Connections, 14 SEER, 11 EER, 2 - 5 Ton

Q7RE
Single Packaged Heat Pump, Round Duct Connections, 14 SEER, 8.0 HSPF, 11 EER, 2 - 5 Ton



ENERGY STAR® certification is awarded to products designed to reduce energy consumption and utility costs.

To qualify, packaged systems must have a Seasonal Energy Efficiency Ratio (SEER) rating of 15.0 or higher and an Energy Efficiency Ratio (EER) of 12.0 or higher. Packaged heat pumps must also have a Heating Seasonal Performance Factor (HSPF) of 8.2 or higher.

Split system air conditioners and heat pumps must have a 15.0 SEER rating or higher and an EER of 12.5 or higher. Split system heat pumps must also have an HSPF of 8.5 or higher.





10 YEAR WARRANTY

NuTone units offer a 10 year limited warranty on all parts when registered. Plus the NuTone Quality Pledge on select models, which states if within the first 10 years the compressor or furnace heat exchanger fails NuTone will replace the entire unit, registration required. ES/ET models carry a 1-year Quality Pledge when registered. Air handlers and coils carry a 5-year all parts limited warranty and when installed with a matched outdoor unit, will carry the outdoor system warranty. J models carry a 5-year all parts limited warranty and a 5-year compressor warranty. See warranty for details.

QUALITY PLEDGE

Split System Air Conditioners

iQ Drive®

ecoLogic®

FS4BG
Ultra High Efficiency, 20 SEER, Air Conditioner, iQ Drive® Technology, 2, 3, 4 and 5 Ton Capacity, Micro-Channel



FS4BF
Extra High Efficiency, Up to 16 SEER, 2-Stage, Air Conditioner, 2, 3, 4 and 5 Ton Capacity, Micro-Channel



ES6BF
Extra High Efficiency, Up to 16 SEER, 1-Stage, Air Conditioner, 2, 2-1/2, 3, 3-1/2 and 4 Ton Capacity, Micro-Channel



FS4BE/ES4BE
High Efficiency, Up to 15 SEER, Air Conditioner, 1-1/2 - 5 Ton Capacity, Micro-Channel

FS4BD/ES4BD
High Efficiency, Up to 14 SEER, Air Conditioner, 1-1/2 - 5 Ton Capacity, Micro-Channel



JS6BE
High Efficiency, Up to 15 SEER, Builder's Series, Air Conditioner, 1-1/2 - 3 Ton Capacity, Micro-Channel

JS6BD
High Efficiency, Up to 14 SEER, Builder's Series, Air Conditioner, 1-1/2 - 3 Ton Capacity, Micro-Channel



Split System Heat Pumps

iQ Drive®

ecoLogic®

FT4BG
Ultra High Efficiency, Up to 19 SEER, 10.0 HSPF, Heat Pump, iQ Drive Technology, 2, 3, 4 and 5 Ton Capacity



FT4BF/ET4BF
Extra High Efficiency, Up to 16 SEER, 9.0 HSPF, 2-Stage, Heat Pump, 2, 3, 4 and 5 Ton Capacity



FT4BE/ET4BE
High Efficiency, Up to 15 SEER, 8.5 HSPF, Heat Pump, 1-1/2 - 5 Ton Capacity, Micro-Channel

JT6BE
High Efficiency, Up to 15 SEER, 8.2 HSPF, Heat Pump, 2 - 3-1/2 Ton Capacity, Micro-Channel



* FT4BF models only are rated ecoLogic

Geothermal Split System Heat Pumps

Y1SA
EarthDirEX™ Geothermal Direct Geoexchange, 19.0 - 22.0 EER, 3.8 - 4.0 COP, Cooling capacity 24,000 - 60,000, Heating capacity 21,000 - 57,000



Air Handlers

B6VMAX
Multi-Poised, Vertical/ Horizontal, Variable-Speed, Air Handler, TXV, Anteater®

B6BMMX
Multi-Poised, Vertical/ Horizontal, Multi-Speed, Air Handler, TXV, Anteater MC® Micro-Channel

B6BMM0
Multi-Speed, Multi-Poised, Air Handler, Anteater MC Micro-Channel

B6EMMX
ECM Fixed-Speed Motor, Multi-Poised, Air Handler, TXV, Anteater MC Micro-Channel

B6VMMX
ECM Variable-Speed Motor, Multi-Poised, Air Handler, TXV, Anteater MC Micro-Channel

B6BW
Vertical Wall Mount, Air Handler, Anteater MC Micro-Channel

B6EW
Vertical Wall Mount, Multi-Speed, ECM Motor, Air Handler, TXV, Anteater MC Micro-Channel





MB7BM
Multi-Poised, Multi-Speed Modular Blower
(matched with a cased coil easily creates a 2 piece Air Handler)

MB7EM
Energy Efficient Model

MB7VM
Variable-Speed Model



Indoor Coils

C7B(A, H)M0
Anteater MC Micro-Channel A, B, C and D sizes available in various capacities

Cased & Uncased, Vertical/Horizontal Multi-poised versions available

C7B(A, H)MX
Factory-installed TXV, Anteater MC Micro-Channel A, B, C and D sizes available in various capacities

Cased & Uncased, Vertical/Horizontal Multi-poised versions available

C6BH-X
A, B, C and D sizes available in various capacities, Anteater

Cased, Uncased & Horizontal versions available



System Accessories

Air Cleaners

Electronic Air Cleaner
Lifetime filtering systems, removes household allergens and pollutants down to .01 microns

Media Air Cleaner
MERV 14, long life media filter, removes airborne particles down to 0.3 microns

1" Electronic Air Cleaner
Easy to maintain, 24V, 95% efficient down to .01 microns



System Accessories

Air Cleaners continued

HEPA Air Cleaner
High efficiency air filtration, captures 99.97% of harmful airborne pollutants

UV Air Treatment Systems

UV object purifiers and Photo Catalytic Oxidation (PCO) units remove mold, bacteria, and viruses that are found in the air stream and also remove odors from the home

Thermostats

Universal, Programmable 7-day, 24V, digital, up to 3 heat/2 cool, backlit display + keypad, auto or manual changeover

Humidifiers

Eliminates parched, dry air which can cause dry nose & throat, itchy & dry skin by delivering humidity and reducing static electricity

Zoning

Total comfort for every room by creating custom comfort zones



NuTone®

Specifications and illustrations subject to change without incurring obligation.

www.nutonehvac.com

NuTone® trademark used under license. iHybrid®, iQ Drive®, iSEER®, ecoLogic®, SmartLite®, Anteater® and Anteater MC® are registered trademarks of Nortek Global HVAC, LLC. EarthDirEX™ is a trademark of Nortek Global HVAC, LLC. © Nortek Global HVAC, LLC 2016. All Rights Reserved. Printed in U.S.A. 696C-0416