



UVF-36

STANDARD FEATURES

Traditional pattern brick liner (back and sides) offers custom masonry look


Charcoal finish canopy

Mesh draw screens

Durable charcoal powder coat finish

Easy gas line access with knockouts on both sides

FRAMING DIMENSIONS Back Wall of Chase/enclosure Including Finishing Materials If Any Corner Installation 44-3/16" (1122) 31-3/4" (286) (807) 23-9/16 42-1/4" (1073) -Rough Framing Face (unfinished Shown) 63-1/2" (1613) Rough Framing Face (unfinished Shown) Header 23-9/16 42-1/4" (1073) Parallel (599)40-1/4" (1022) 20-1/2' (521) * Back Wall of Chase/Enclosure Including Finishing Materials If Any



OPTIONAL ACCESSORIES

Forced air blower kit

Decorative mesh screen door (Textured Iron finish shown in cover photo)

Outside air kit

Wall switch

Junction box (required for forced air blower kit)

Cover photo: UVF-36 shown with optional decorative mesh screen door and VFGL-24-4 gas logs

NOTE: Diagrams and illustrations are not to scale and should not be used for framing purposes – consult installation instructions. Product designs, materials, dimensions, specifications, colors and prices subject to change or discontinuance without notice.

LISTING: These Universal Vent-Free (built-in) Fireboxes have been tested and listed as Ventless Firebox Enclosures for Gas-Fired Unvented Decorative Room Heaters to ANSI Z21.91.

APPROVED GAS LOGS: These appliances are listed for use ONLY with Vent-Free Gas Log Room Heaters listed to ANSI Z21.11.2 which have an input not to exceed 40,000 BTU/Hr.





©Lennox Industries Inc. 2007 Visit us at www.Lennox.com, or contact us at 1-800-9-LENNOX.