Gibson®

Product Line

with SEER2/HSPF2 Efficiency Standards

Up to 96% AFUE Gas Furnaces

All gas furnaces except KG8SA & FG8SD feature SmartLite® Control Boards



KG7TE-FS, KG7TN-FS
Up to 96% AFUE Ultra High Efficiency, Direct Vent or Non-Direct Vent, Condensing, 2-Stage, (Dedicated Upflow), (Downflow), Multi-Speed ECM Blower Motor, (35,000 - 115,000), (60,000 - 115,000) BTUH Input

Up to 95%+ AFUE Ultra-Low NOx Gas Furnaces



FG8SD-FS
Up to 95%+ AFUE Ultra-Low NOx, High Efficiency, 1-Stage Upflow/Horizontal, Multi-Speed ECM Blower Motor, 50,000 - 100,000 BTUH Input

Up to 95% AFUE Gas Furnaces



KG7TC-FS
Up to 95% AFUE High Efficiency, Direct Vent or Non-Direct Vent, Condensing, 2-Stage Upflow/Horizontal, Multi-Speed ECM Blower Motor, 60,000 - 120,000 BTUH Input



KG7SD-FS
Up to 95% AFUE High Efficiency, Direct Vent or Non-Direct Vent, Condensing, 1-Stage, Upflow/ Horizontal, Multi-Speed ECM Blower Motor, 38,000 - 120,000, BTUH Input

Up to 92% AFUE Gas Furnaces



KG7SC-FS
Up to 92% AFUE High Efficiency, Direct Vent or Non-Direct Vent, Condensing, 1-Stage, Upflow/ Horizontal, Multi-Speed ECM Blower Motor, 38,000 - 120,000 BTUH Input

Up to 80% AFUE Ultra-Low NOx Gas Furnaces



KG8SA-FS
Up to 80% AFUE Ultra-Low NOx, Standard Efficiency, 1-Stage Upflow/Horizontal, Multi-Speed ECM Blower Motor, 55,000 - 100,000 BTUH Input

Up to 80% AFUE Gas Furnaces



KG7TA-FS
Up to 80% AFUE Mid Efficiency, 2-Stage, Upflow/Horizontal, Multi-Speed ECM Blower Motor, 60,000 - 120,000 BTUH Input



KG7SA-FS
Up to 80% AFUE Standard Efficiency, 1-Stage Upflow/ Horizontal, Multi-Speed ECM Blower Motor, 45,000 - 126,000 BTUH Input

KG7SK-FS
Up to 80% AFUE Standard Efficiency, 1-Stage Downflow, Multi-Speed ECM Blower Motor, 54,000 - 126,000 BTUH Input

Convertible Airflow Packaged Systems

All packaged systems feature enhanced coil technology

R104HD
Gas/Electric, 2-Stage Heat, SmartLite Control Board, Square Duct Connections, Convertible Airflow, 13.4 SEER2, 95% AFUE, 2 - 5 Ton, 60,000 - 96,000 BTUH Input



Convertible Airflow Packaged Systems continued

R104GD
Single Packaged Gas/Electric, SmartLite Control Board, Square Duct Connections, Convertible Airflow, 13.4 SEER2, 81% AFUE, 2 - 5 Ton, 45,000 - 120,000 BTUH Input



R104GD-U
Ultra-Low NOx, Single Packaged Gas/Electric, Square Duct Connections, Convertible Airflow, 13.4 SEER2, 81% AFUE, 2 - 5 Ton, 55,000 - 100,000 BTUH Input



Q104SD
Single Packaged Heat Pump, Square Duct Connections, Convertible Airflow, 13.4 SEER2, 6.7 HSPF2, 2 - 5 Ton



Horizontal Airflow Packaged Systems

P94RD
Single Packaged Air Conditioner, Round Duct Connections, Horizontal Airflow, 13.4 SEER2, 2 - 5 Ton



Q94RD
Single Packaged Heat Pump, Round Duct Connections, Horizontal Airflow, 13.4 SEER2, 6.7 HSPF2, 2 - 5 Ton





Split Systems Air Conditioners

WSA3BE
High Efficiency, Up to 14.3 SEER2, Air Conditioner, Single-Stage, 1-1/2 - 5 Ton Capacity



WSA3BD
High Efficiency, 13.4 SEER2, Single-Stage, Air Conditioner, 1-1/2 - 5 Ton Capacity



Split Systems Heat Pumps

WSH3BE
High Efficiency, 14.3 SEER2, 7.5 HSPF2, Single-Stage, Heat Pump, 1-1/2 - 5 Ton Capacity



GXH(_)(_)MSK4DH
High Efficiency Inverter Driven, Up to 17 SEER2, Side Discharge, 2-5 Ton Capacity



Air Handlers

B64VMMX
2-Stage, ECM Variable-Speed Motor, Multi-Poised, Air Handler, TXV

B64EMMX
ECM Fixed-Speed Motor, Multi-Poised, Air Handler, TXV

B64BMMX
PSC Motor, Multi-Poised, Vertical/ Horizontal, Multi-Speed, Air Handler, TXV



B64BMMO
PSC Motor, Fixed Orifice, Multi-Speed, Multi-Poised, Air Handler

B64EW
ECM Motor, Vertical Wall Mount, Air Handler, TXV



GMH
Multi-Poised, Vertical/ Horizontal, High Static, Air Handler for the Ultra Side Discharge Condenser



Air Handlers continued

MB7VM
Modular , Variable-Speed Model (matched with a cased coil easily creates a 2 piece Air Handler)



Indoor Coils

C74BAM0
Vertical, Fixed Orifice, Cased, Uncased
A, B, C and D sizes available in various capacities



C74BHM0
Horizontal, Fixed Orifice, Cased,
A, B, C and D sizes available in various capacities



C74BAMX
Vertical, TXV, Cased,
A, B, C and D sizes available in various capacities



C74BHMX
Horizontal, TXV, Cased, A, B, C and D sizes available in various capacities



SEER2, HSPF2 & EER2 REQUIREMENTS

ENERGY STAR® certification is awarded to products designed to reduce energy consumption and utility costs.

Packaged systems must have a Seasonal Energy Efficiency Ratio 2 (SEER2) rating of 15.2 and an Energy Efficiency Ratio 2 (EER2) of 11.5. Packaged heat pumps in the south must have a SEER2 rating of 15.2, Heating Seasonal Performance Factor 2 (HSPF2) of 7.2 and an Energy Efficiency Ratio 2 (EER2) of 10.6. Packaged heat pumps in the north must have a SEER2 rating of 15.2, Heating Seasonal Performance Factor 2 (HSPF2) of 8.1 and an Energy Efficiency Ratio 2 (EER2) of 10.0.

Split system air conditioners must have a 15.2 SEER2 rating and an EER2 of 12.0. Split system heat pumps south must have a 15.2 SEER2 rating, an HSPF2 of 7.8 and an EER2 of 11.7. Split system heat pumps north must have a 15.2 SEER2 rating, an HSPF2 of 8.1 and an EER2 of 10.0.

AFUE REQUIREMENTS

To qualify, gas furnaces must have an AFUE of 97%.

10 YEAR WARRANTY Gibson

Gibson split system air conditioners and heat pumps offer a 10-Year limited warranty that covers all parts when registered as part of a complete Gibson system. Air handlers and coils carry a 3-Year all parts limited warranty and when installed with a matched outdoor unit, will carry the outdoor system warranty. All Gibson gas furnaces and packaged systems offer a 10-Year limited warranty that covers all parts when registered. Additionally, Gibson gas furnaces and gas/electric packaged systems carry a limited lifetime warranty on the heat exchanger. To learn more about our product warranties, ask your Gibson contractor.

Gibson ductless mini-split systems offer a 5-Year limited parts warranty, compressors carry a 7-Year warranty.

Flex Match Mini Split Heat Pump Systems

GXH_(_)FMK4DH-1
Up to 21 SEER2, up to 10.0 HSPF2,
1 to 5 IDUs, 18K to 42K BTU,
Multi-Zone, Mini Split Heat Pump ODU,
208/230 Volt, 60 Hz, 1-Phase




GHH_(_)LUK4DH2
Up to 21 SEER2, 9K to 24K BTU,
Multi-Zone, Mini Split Wall Mount IDU,
208/230 Volt, 60 Hz, 1-Phase



GDH_(_)FMK4DH
Up to 21 SEER2, 9K to 24K BTU,
Multi-Zone, Mini Split Ducted IDU,
208/230 Volt, 60 Hz, 1-Phase



GKH_(_)FMK4DH
Up to 21 SEER2, 9K to 24K BTU,
Multi-Zone, Mini Split 4-Way Cassette
IDU, 208/230 Volt, 60 Hz, 1-Phase



GCH_(_)FMK4DH
Up to 21 SEER2, 9K to 24K BTU,
Multi-Zone, Mini Split Console IDU,
208/230 Volt, 60 Hz, 1-Phase



Mini Split Remotes & Controllers

WLRC17
Remote Wireless, All 17 SEER2, Single Zone
and 30K/36K, 25 SEER2, Single Zone



WLRC18
Remote Wireless, 09K - 24K, 25 SEER2, Single
Zone



WLRC3
Remote, Wireless, Flex Match for Ducted
and Cassette IDUs



WLRC6
Remote, Wireless, Flex Match for Console
IUDs



WRC3
Controller, Wired, Flex Match for Ducted
and Cassette IDUs



Mini Split Heat Pump Systems

GXH_(_)LSK4DH2
Up to 25 SEER2, up to 12.0 HSPF2, 9K to 36K BTU, Single-Zone, Mini Split Heat Pump ODU, 208/230 Volt, 60 Hz, 1-Phase



GHH_(_)LUK4DH2
Up to 25 SEER2, up to 12.0 HSPF2, 9K to 36K BTU, Single-Zone, Mini Split Wall Mount IDU, 208/230 Volt, 60 Hz, 1-Phase



GXH_(_)LSK4DL2
Up to 18 SEER2, up to 9.5 HSPF2, 9K to 24K BTU, Single-Zone, Mini Split Heat Pump ODU, 230 Volt, 60 Hz, 1-Phase



GHH_(_)LSK4DL2
Up to 18 SEER2, up to 9.5 HSPF2, 9K to 24K BTU, Single-Zone, Mini Split Wall Mount IDU, 230 Volt, 60 Hz, 1-Phase



GXH_(_)LSA4DL2
Up to 18 SEER2, up to 9.5 HSPF2, 9K to 12K BTU, Single-Zone, Mini Split Heat Pump ODU, 115 Volt, 60 Hz, 1-Phase



GHH_(_)LSA4DL2
Up to 18 SEER2, up to 9.5 HSPF2, 9K to 12K BTU, Single-Zone, Mini Split Wall Mount IDU, 115 Volt, 60 Hz, 1-Phase



Gas Furnace, Packaged System & Split System Accessories

Air Cleaners

Electronic Air Cleaner
Lifetime filtering systems, removes household allergens and pollutants down to .01 microns



Media Air Cleaner
MERV 14, long life media filter, removes airborne particles down to 0.3 microns



1" Electronic Air Cleaner
Easy to maintain, 24V, 95% efficient down to .01 microns



HEPA Air Cleaner
High efficiency air filtration, captures 99.97% of harmful airborne pollutants



Thermostats

Universal, Programmable
7-day, 24V, digital, up to 3 heat/2 cool, backlit display + keypad, auto or manual changeover



Gibson®

Specifications and illustrations subject to change without incurring obligation.

www.gibsonhvac.com

Gibson® is a registered trademark used under license from Gibson International Company, U.S.A. SmartLite® is a registered trademark of Nortek Global HVAC, LLC. © Nortek Global HVAC, LLC 2023. All Rights Reserved. Printed in U.S.A.

833F-0623