MANUFACTURED HOUSING

SERIAL NUMBER INTERPRETER

XX P YY MM SSSSSS

- **XX** — 1st Digits of Model
- **P** — Manufacturing Plant
  - D = Poplar Bluff F = Dyersburg
  - G = Saltillo
- **YY** — Year Manufactured
- **MM** — Month Manufactured
- **SSSSSS** — Sequence Number

M G 1 E - 056 F 1 A B M 2

- **M** — Manufactured Housing
- **G** — Gas Furnace
- **1** — 1,2 = Manufactured Housing Footprint; 3 = Residential Footprint
- **E** — Efficiency
  - E = 80% AFUE R = 95% AFUE
  - P = 92% AFUE S = 96% AFUE
- **056** — Input Heating Capacity (BTU)
  - 056 = 56,000
  - 070 = 70,000
  - 077 = 77,000
  - 080 = 80,000
  - 090 = 90,000
- **F** — T = Top Return Downflow; F = Front Return Downflow; U = Upflow
- **1** — 1 = Single Stage; 2 = Two Stage
- **A** — A = 120V, 1 Phase, 60 Hz
- **B** — A = No Evaporator Coil Cabinet; B = Cabinet fits 18" nominal coil heights
- **M** — Cabinet Width
  - M = Manufactured Housing
  - B = 17.5"
  - C = 21.0"
  - D = 24.0"
- **2** — Revision

C M F 3 - 70 T - P G

- **CMF** — 18" CMF Footprint
- **3** — AFUE
  - 3 = 80%
  - 95 = 95%
- **70** — Input Heating Capacity (BTU)
  - 045 = 45,000
  - 070 = 70,000
  - 072 = 72,000
- **T** — FER Compliant
- **PG** — PG = Power Gas; PO = Power Oil Gun Burners

M 5 S B - 0 6 6 A - B W 2

- **M** — Manufactured Housing
- **5** — Furnace Series
- **S** — Fuel, Type of Combustion
  - S = Oil, Direct Vent, Gun Burner
- **B** — Comfort Model
  - B = A/C Ready, 3 Ton
  - C = A/C Ready, 4 Ton
- **066** — Heating Capacity Input MBTUH
- **A** — A = 120V, 1 Phase, 60 Hz
- **B** — Cabinet Dimensions
  - A = 56" x 19-3/4" x 23-3/4"
  - B = w/Coil Cavity, 76" x 19-3/4" x 23-3/4"
- **W** — Door Color
  - W = White
- **2** — Revision

E 7 E M - 010 H 2

- **E** — Product Type
  - E = Electric Furnace
- **7** — Generation
  - 7 = Seventh Series
- **E** — Blower
  - E = Constant Torque 16 Speed ECM
- **M** — Blower
  - M = Multiposition
  - D = Downflow
  - U = Upflow
- **010** — Primary Capacity
  - 010 - 10 kw 017 - 17 kw
  - 012 - 12 kw 020 - 20 kw
  - 015 - 15 kw 023 - 23 kw
- **H** — Electrical Code
  - H = 240-1-60
- **2** — Revision

GSA3ME4M1SN18K

Split System

A = Air Conditioner
H = Heat Pump

Design Series
3 = SEER2

M = Brazed Fittings
Q = Quick Connect Fittings

D = 13.4 SEER2
E = 13.8/14.3 SEER2

Refrigerant
4 = R-410A

Stages
1 = Single
2 = Two

Compressor
R = Rotary
S = Scroll

C = Copper Coil
M = Micro-Channel

Metering Device
N = None
P = Piston
X = TXV

Size (MBTU)

Voltages
K = 208/230-1-60

B64BM036K-B

Indoor Air Handler

Design Series

Refrigerant
4 = R-410A

Motor:
B = 3, 4 or 5-speed

Configuration:
M = Multipoise

Metering Device:
X = TXV
0 = Piston

Nominal Capacity
(00) Btuh

Electrical Code
K = 208/230-60-1

Cabinet Identifier
A = 14.25" Width
B = 19.75" Width
C = 22.5" Width

C84DAM036U-B

Coil

Design Series

Refrigerant
4 = R-410A

D = Down Turn Braze Connections
Q = Down Turn Quick Connections

A = "A" Vertical

M = Micro-Channel

Metering Device
X = TXV
0 = Orifice

Nominal Capacity/Range
(00,000) Btuh

U = Uncased Coil

Cabinet Identifier
B = 19 3/4" Width

R104GD048K096CA

Application
R = Packaged Gas/Electric

Design Series
6,8 = Convertible Sideshot/Downshot
10 = SEER2 Convertible Sideshot/Downshot

Refrigerant
4 = R-410A

G = Gas/Electric
H = 95% AFUE
S = Square Duct

Efficiency
D = 13.4 SEER2

X = TXV
0 = Orifice

Nominal Cooling Capacity
(00) Btuh

Electrical Code
K = 208/230-1-60

Heating Capacity
(000) Btuh Input

C = Standard
X = NOx Approved

Revision

P94RD-036K

Application
P = Packaged Air Conditioner
Q = Packaged Heat Pump

Design Series
9 = SEER2 Horizontal Supply/Return
10 = SEER2 Convertible Sideshot/Downshot

Refrigerant
4 = R-410A

Duct Configuration
R = Round Duct

Efficiency
D = 13.4 SEER2

X = TXV
0 = Orifice

Nominal Capacity
(00) Btuh

Electrical Code
K = 208/230-1-60