

# **MPE-27**


## **Framing Specifications**



Note: Framing dimensions are calculated for an in front of the wall front face installation with finish dry wall in place.



Front View



# **Fireplace Dimensions**

### **Fireplace Specifications**

Cat. No.: H3428 Model: MPE-27 Description:

Merit Plus Electric Fireplace - 27" Shipping Weight: 78 lb.'s (35 KG)

Packaging:

34 1/2" x 14" x 34"

(876 mm x 356 mm x 864 mm)

14.1 cu. ft.

Power Requirements:

(120 Volt, 60 Hz.)


Rated Wattage - 1600 Watts


Amperage - 15 Amps

Blower CFM: 83 CFM (120 V): 5,461 BTU/HR


Specifications and clearances are subject to change without notice. Refer to the Installation Instructions before installation of this appliance for updated dimensions instructions.

NOTE: DIAGRAMS & ILLUSTRATIONS NOT TO SCALE.





Front View



**Right Side** 



### **MPE-27**

#### Minimum Clearances to Combustibles

Sides:	25.5 mm - 1 inch
Floor:	25.5 mm - 1 inch
Top:	25.5 mm - 1 inch

**Mantel Clearance:** Combustible and Noncombustible mantels may be installed at any height above the top of the face of fireplace.

Hearth Protection: A hearth is not mandatory, but may be used for aesthetic purposes. Secure the hearth extension to the floor to prevent possible shifting. Do no block the airflow beneath the appliance.


#### **Fireplace Controls**

This Merit Plus Electric Fireplace is provided with an Infrared light Remote Control. All functions of the fireplace can be controlled through the remote control.

**Note:** The effective range of the remote control is up to approximately 25 feet (8 meters). Manual Controls are also provided on the appliance.



**Remote Control** 



**Manual Controls** 

### **Fireplace Features**

- Plug-In Ready With Standard Three Pronged 110V Grounded Power Cord Makes Installation Easy.
- On/Off Switch, Adjustable Flames/ Ember Beds And Easy-To-Use Heater Temperature Settings Provides Customized Control.
- Adjustable Flame And Ember Intensity Provide Customizable Fire Presentation.
- Remote Control Adds Convenience.



CSA Report No. 46-M198



Standard 5,000 BTU Heater/
Blower With Three Built-in
Thermostatic Settings Delivers
Measured Warmth To Any
Room Environment

Bronze-Tinted Flush Panel Glass Door Adds A Touch Of Elegance And Realism

Charred Split Oak Log Set With Glowing Ember Bed Featuring Exclusive Lennox Glowing Ember Crystals

Easy-Access Manual Controls Mounted On The Unit Makes Operation Simple

